Internet Draft
Expires August 21, 1996
File: draft-ietf-rsvp-spec-10.ps

R. Braden, Ed.
ISI
L. Zhang
PARC
S. Berson
ISI
S. Herzog
ISI
S. Jamin
USC

February 1996

Resource ReSerVation Protocol (RSVP) – Version 1 Functional Specification

February 21, 1996

Status of Memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

To learn the current status of any Internet-Draft, please check the "1id-abstracts.txt" listing contained in the Internet- Drafts Shadow Directories on ds.internic.net (US East Coast), nic.nordu.net (Europe), ftp.isi.edu (US West Coast), or munnari.oz.au (Pacific Rim).

Abstract

This memo describes version 1 of RSVP, a resource reservation setup protocol designed for an integrated services Internet. RSVP provides receiver-initiated setup of resource reservations for multicast or unicast data flows, with good scaling and robustness properties.

Contents

1 Introduction 4
1.1 Data Flows . . . 6
1.2 Reservation Model . . . 7
1.3 Reservation Styles . . . 9
1.4 Examples of Styles . . . 12
2 RSVP Protocol Mechanisms **16**
2.1 RSVP Messages . . . 16
2.2 Port Usage . . . 17
2.3 Merging Flowspecs . . . 18
2.4 Soft State . . . 19
2.5 Teardown . . . 21
2.6 Errors . . . 22
2.7 Confirmation . . . 23
2.8 Policy and Security . . . 24
2.9 Automatic RSVP Tunneling . . . 25
2.10 Host Model . . . 26
3 RSVP Functional Specification **27**
3.1 RSVP Message Formats . . . 27
3.2 Sending RSVP Messages . . . 39
3.3 Avoiding RSVP Message Loops . . . 40
3.4 Blockade State . . . 43
3.5 Local Repair . . . 44
3.6 Time Parameters . . . 45
3.7 Traffic Policing and Non-Integrated Service Hops . . . 47
3.8 Multihomed Hosts . . . 48
3.9 Future Compatibility . . . 49
3.10 RSVP Interfaces . . . 51
4 Message Processing Rules **61**
5 Acknowledgments **75**
A Object Definitions **76**
A.1 SESSION Class . . . 76
A.2 RSVP_HOP Class . . . 78
A.3 INTEGRITY Class . . . 79
A.4 TIME_VALUES Class . . . 79
A.5 ERROR_SPEC Class . . . 80
A.6 SCOPE Class . . . 82
A.7 STYLE Class . . . 83
A.8 FLOWSPEC Class . . . 84
A.9 FILTER_SPEC Class . . . 85

A.10 SENDER_TEMPLATE Class 87
A.11 SENDER_TSPEC Class 87
A.12 ADSPEC Class 88
A.13 POLICY_DATA Class 89
A.14 RESV_CONFIRM Class 90
B Error Codes and Values **91**
C UDP Encapsulation **95**

What's Changed

The most important changes in this document from the rsvp-spec-09 draft are:

- Multiple POLICY_DATA objects in any order are now allowed.
- The length field in the common header is now the total message length [Section 3.1.1].
- The meaning of Message Id is refined and more completely specified [Section 3.1.1].
- RSVP fragmentation is specifically called for, and IP fragmentation disallowed [Section 3.1.1].
- The granularity of state timeouts is now specified [Section 3.6].

The most important changes in this document from the rsvp-spec-08 draft are:

- The handling of reservation errors has been fundamentally changed, to prevent the "second killer reservation problem". A new kind of state has been introduced into a node, "blockade state", which is created by a *ResvErr* message with Error Code = 01, and which controls the merging process for generating reservation refresh messages [Sections 2.6 and 3.4].
- RSVP now carries two flag bits in the SESSION object to indicate to a receiver whether there are non-RSVP-capable nodes along the path to a given sender [Sections 2.9 and 3.7].
- The optional INTEGRITY object is now specified to immediately follow the common header and to appear in every fragment [Section 3.1].
- There are now two flag bits in an ERROR_SPEC object: InPlace and NotGuilty [Section 3.10].
- The text now states that implementations should be as permissive as possible in accepting objects in any order within a message (and required ordering is specified), but they should follow the BNF-implied order in creating a message.
- The text now states that IP fragmentation of data packets is generally not possible when RSVP is in use, since the TCP/UDP port fields may be required for classification [Section 1.2].
- The rules for handling an unrecognized object class are changed to include a third possibility: ignore and do not forward the object [Section 3.9].
- All generic Traffic Control calls are modified to include an interface specification, allowing the Thandle to be interface-specific [Section 3.10.2].
- Disabling an interface for RSVP is allowed [Section 3.10.3].

1 Introduction

This document defines RSVP, a resource reservation setup protocol designed for an integrated services Internet [RSVP93,ISInt93].

The RSVP protocol is used by a host, on behalf of an application data stream, to request a specific quality of service (QoS) from the network. The RSVP protocol is also used by routers to deliver QoS requests to all nodes along the path(s) of the data stream and to establish and maintain state to provide the requested service. RSVP requests will generally, although not necessarily, result in resources being reserved along the data path.

RSVP requests resources for *simplex* data streams, i.e., it requests resources in only one direction. Therefore, RSVP treats a sender as logically distinct from a receiver, although the same application process may act as both a sender and a receiver at the same time. RSVP operates on top of IP (either IPv4 or IP6), occupying the place of a transport protocol in the protocol stack. However, RSVP does not transport application data but is rather an Internet control protocol, like ICMP, IGMP, or routing protocols. Like the implementations of routing and management protocols, an implementation of RSVP will typically execute in the background, not in the data forwarding path, as shown in Figure 1.

RSVP is not itself a routing protocol; RSVP is designed to operate with current and future unicast and multicast routing protocols. An RSVP daemon consults the local routing database(s) to obtain routes. In the multicast case, for example, a host sends IGMP messages to join a multicast group and then sends RSVP messages to reserve resources along the delivery path(s) of that group. Routing protocols determine where packets get forwarded; RSVP is only concerned with the QoS of those packets that are forwarded in accordance with routing.

Each node that is capable of resource reservation passes incoming data packets through a *packet classifier*, which determines the route and the QoS class for each packet. For each outgoing interface, a *packet scheduler* then makes forwarding decisions for each packet to achieve the promised QoS on the particular link-layer medium used by that interface.

If the link-layer medium is QoS-active, i.e., if it has its own QoS management capability, then the packet scheduler is responsible for negotiation with the link layer to obtain the QoS requested by RSVP. This mapping to the link layer QoS may be accomplished in a number of possible ways; the details will be medium-dependent. On a QoS-passive medium such as a leased line, the scheduler itself allocates packet transmission capacity. The scheduler may also allocate other system resources such as CPU time or buffers.

In order to efficiently accommodate heterogeneous receivers and dynamic group membership, RSVP makes receivers responsible for requesting QoS [RSVP93]. A QoS request, which typically originates



Figure 1: RSVP in Hosts and Routers

from a receiver host application, is passed to the local RSVP implementation, shown as a daemon process in Figure 1. The RSVP protocol then carries the request to all the nodes (routers and hosts) along the reverse data path(s) to the data source(s).

At each node, the RSVP daemon communicates with two local decision modules, *admission control* and *policy control*. Admission control determines whether the node has sufficient available resources to supply the requested QoS. Policy control determines whether the user has administrative permission to make the reservation. If both checks succeeds, the RSVP daemon sets parameters in the packet classifier and scheduler to obtain the desired QoS. If either check fails, the RSVP program returns an error notification to the application process that originated the request. We refer to the packet classifier, packet scheduler, and admission control components as *traffic control*.

RSVP is designed to scale well for very large multicast groups. Since both the membership of a large group and the topology of large multicast trees are likely to change with time, the RSVP design assumes that router state for traffic control will be built and destroyed incrementally. For this purpose, RSVP uses "soft state" in the routers. That is, RSVP sends periodic refresh messages to maintain the state along the reserved path(s); in absence of refreshes, the state will automatically time out and be deleted.

RSVP protocol mechanisms provide a general facility for creating and maintaining distributed reservation state across a mesh of multicast or unicast delivery paths. RSVP transfers reservation parameters as opaque data (except for certain well-defined operations on the data), which it simply passes to traffic control for interpretation. Although the RSVP protocol mechanisms are largely independent of the encoding of these parameters, the encodings must be defined in the reservation model that is presented to an application; see Appendix A for more details.

In summary, RSVP has the following attributes:

- RSVP makes resource reservations for both unicast and many-to-many multicast applications, adapting dynamically to changing group membership as well as changing routes.
- RSVP is simplex, i.e., it reserves for a data flow in one direction only.
- RSVP is receiver-oriented, i.e., the receiver of a data flow initiates and maintains the resource reservation used for that flow.
- RSVP maintains "soft state" in the routers, providing graceful support for dynamic membership changes and automatic adaptation to routing changes.
- RSVP provides several reservation models or "styles" (defined below) to fit a variety of applications.
- RSVP provides transparent operation through routers that do not support it.

Further discussion on the objectives and general justification for RSVP design are presented in [RSVP93,ISInt93].

The remainder of this section describes the RSVP reservation services. Section 2 presents an overview of the RSVP protocol mechanisms. Section 3 contains the functional specification of RSVP, while Section 4 presents explicit message processing rules. Appendix A defines the variable-length typed data objects used in the RSVP protocol. Appendix B defines error codes and values. Appendix C defines an extension for UDP encapsulation of RSVP messages. Finally, some experimental RSVP features are documented in Appendix D for future reference.

1.1 Data Flows

RSVP defines a *session* as a data flow with a particular destination and transport-layer protocol. The destination of a session is generally defined by DestAddress, the IP destination address of the data packets, and perhaps by DstPort, a *generalized destination port*, i.e., some further demultiplexing point in the transport or application protocol layer. RSVP treats each session independently, and this document often assumes the qualification "for the same session".

DestAddress is a group address for multicast delivery or the unicast address of a single receiver. DstPort could be defined by a UDP/TCP destination port field, by an equivalent field in another transport protocol, or by some application-specific information. Although the RSVP protocol is designed to be easily extensible for greater generality, the present version supports only UDP/TCP ports as generalized ports.

Note that it is not strictly necessary to include ports in the session definition when DestAddress is multicast, since different sessions can always have different multicast addresses. However, destination ports are necessary to allow more than one unicast session to the same receiver host.

Figure 2 illustrates the flow of data packets in a single RSVP session, assuming multicast data distribution. The arrows indicate data flowing from senders S1 and S2 to receivers R1, R2, and R3, and the cloud represents the distribution mesh created by multicast routing. Multicast distribution forwards a copy of each data packet from a sender Si to every receiver Rj; a unicast distribution session has a single receiver R. Each sender Si may be running in a unique Internet host, or a single host may contain multiple senders, distinguished by generalized source ports.



Figure 2: Multicast Distribution Session

For unicast transmission, there will be a single destination host but there may be multiple senders; RSVP can set up reservations for multipoint-to-single-point transmission.

1.2 Reservation Model

An elementary RSVP reservation request consists of a *flowspec* together with a *filter spec*; this pair is called a *flow descriptor*. The flowspec specifies a desired QoS. The filter spec, together with a session specification, defines the set of data packets – the "flow" – to receive the QoS defined by the flowspec. The flowspec is used to set parameters to the node's packet scheduler (assuming that admission control succeeds), while the filter spec is used to set parameters in the packet classifier.

Data packets that are addressed to a particular session but do not match any of the filter specs for that session are handled as best-effort traffic.

Note that the action to control QoS occurs at the place where the data enters the medium, i.e., at the upstream end of the link, although an RSVP reservation request originates from receiver(s) downstream. In this document, we define the directional terms "upstream" vs. "downstream", "previous hop" vs. "next hop", and "incoming interface" vs "outgoing interface" with respect to the direction of data flow.

The flowspec in a reservation request will generally include a service class and two sets of numeric parameters: (1) an *Rspec* (R for 'reserve') that defines the desired QoS, and (2) a *Tspec* (T for 'traffic') that describes the data flow. The formats and contents of Tspecs and Rspecs are determined by the integrated service model [ServTempl95a], and are generally opaque to RSVP.

In the most general approach [RSVP93], filter specs may select arbitrary subsets of the packets in a given session. Such subsets might be defined in terms of senders (i.e., sender IP address and generalized source port), in terms of a higher-level protocol, or generally in terms of any fields in any protocol headers in the packet. For example, filter specs might be used to select different subflows in a hierarchically-encoded signal by selecting on fields in an application-layer header. In the interest of simplicity (and to minimize layer violation), the present RSVP version uses a much more restricted form of filter spec, consisting of sender IP address and optionally the UDP/TCP port number SrcPort.

Because the UDP/TCP port numbers are used for packet classification, each router must be able to examine these fields. As a result, it is generally necessary to avoid IP fragmentation of a data stream for which a resource reservation is desired.

RSVP reservation request messages originate at receivers and are passed upstream towards the sender(s). At each intermediate node, two general actions are taken on the request.

1. Make a reservation

   The request is passed to admission control and policy control. If either test fails, the reservation is rejected and RSVP returns an error message to the appropriate receiver(s). If both succeed, the node uses the flowspec to set up the packet scheduler for the desired QoS and the filter spec to set the packet classifier to select the appropriate data packets.

2. Forward the request upstream

   The reservation request is propagated upstream towards the appropriate senders. The set of sender hosts to which a given reservation request is propagated is called the *scope* of that request.

The reservation request that a node forwards upstream may differ from the request that it received from downstream, for two reasons. First, it is possible in theory for the traffic control mechanism to modify the flowspec hop-by-hop, although none of the currently defined services does so. Second, reservations for the same sender, or the same set of senders, from different downstream branches of the multicast tree(s) are *merged* as reservations travel upstream; a node forwards upstream only the reservation request with the "maximum" flowspec.

When a receiver originates a reservation request, it can also request a confirmation message to indicate that its request was (probably) installed in the network. A successful reservation request propagates upstream along the multicast tree until it reaches a point where an existing reservation is equal or greater than that being requested. At that point, the arriving request is merged with the reservation in place, and need not be forwarded further, and the node may then send a reservation confirmation message back to the receiver. Note that the receipt of a confirmation is only a high-probability indication, not a guarantee, that the requested service is in place all the way to the sender(s), as explained in Section 2.7.

The basic RSVP reservation model is *one pass*: a receiver sends a reservation request upstream, and each node in the path either accepts or rejects the request. This scheme provides no easy way for a receiver to find out the resulting end-to-end service. Therefore, RSVP supports an enhancement to one-pass service known as *One Pass With Advertising* (OPWA) [Shenker94]. With OPWA, RSVP control packets are sent downstream, following the data paths, to gather information that may be used to predict the end-to-end QoS. The results ("advertisements") are delivered by RSVP to the receiver hosts and perhaps to the receiver applications. The advertisements may then be used by the receiver to construct, or to dynamically adjust, an appropriate reservation request.

1.3 Reservation Styles

A reservation request includes a set of options, which are collectively called the reservation *style*.

One reservation option concerns the treatment of reservations for different senders within the same session: establish a *distinct* reservation for each upstream sender, or else make a single reservation that is *shared* among all packets of selected senders.

Another reservation option controls the selection of senders: an *explicit* list of all selected senders, or a *wildcard* that implicitly selects all the senders to the session. In an explicit sender-selection reservation, each filter spec must match exactly one sender, while in a wildcard sender-selection no filter spec is needed.

The styles currently defined are as follows (see Figure 3):



Figure 3: Reservation Attributes and Styles

- Wildcard-Filter (WF) Style

  The WF style implies the options: *shared* reservation and *wildcard* sender selection. Thus, a WF-style reservation creates a single reservation into which flows from all upstream senders are mixed. This reservation may be thought of as a shared "pipe", whose "size" is the largest of the resource requests from all receivers, independent of the number of senders using it. A WF-style reservation is propagated upstream towards all sender hosts, and automatically extends to new senders as they appear.

  Symbolically, we can represent a WF-style reservation request by:

  ```
  WF( * {Q})
  ```

  where the asterisk represents wildcard sender selection and Q represents the flowspec.

- Fixed-Filter (FF) Style

  The FF style implies the options: *distinct* reservations and *explicit* sender selection. Thus, an elementary FF-style reservation request creates a distinct reservation for data packets from a particular sender, not sharing them with other senders' packets for the same session.

  The total reservation on a link for a given session is the total of the FF reservations for all requested senders. On the other hand, FF reservations requested by different receivers Rj but selecting the same sender Si must be merged to share a single reservation.

  Symbolically, we can represent an elementary FF reservation request by:

  ```
  FF( S{Q})
  ```

where S is the selected sender and Q is the corresponding flowspec; the pair forms a flow descriptor. RSVP allows multiple elementary FF-style reservations to be requested at the same time, using a list of flow descriptors:

```
FF( S1{Q1}, S2{Q2}, ...)
```

- Shared Explicit (SE) Style

  The SE style implies the options: *shared* reservation and *explicit* sender selection. Thus, an SE-style reservation creates a single reservation into which flows from all upstream senders are mixed. However, like the FF style, the SE style allows a receiver to explicitly specify the set of senders.

  We can represent an SE reservation request containing a flowspec Q and a list of senders S1, S2, ... by:

```
SE( (S1,S2,...){Q} )
```

Both WF and SE styles create shared reservations, appropriate for those multicast applications whose properties make it unlikely that multiple data sources will transmit simultaneously. Packetized audio is an example of an application suitable for shared reservations; since a limited number of people talk at once, each receiver might issue a WF or SE reservation request for twice the bandwidth required for one sender (to allow some over-speaking). On the other hand, the FF style, which creates independent reservations for the flows from different senders, is appropriate for video signals.

The RSVP rules disallow merging of shared reservations with distinct reservations, since these modes are fundamentally incompatible. They also disallow merging explicit sender selection with wildcard sender selection, since this might produce an unexpected service for a receiver that specified explicit selection. As a result of these prohibitions, WF, SE, and FF styles are all mutually incompatible.

It would seem possible to simulate the effect of a WF reservation using the SE style. When an application asked for WF, the RSVP daemon on the receiver host could use local path state to create an equivalent SE reservation that explicitly listed all senders. However, an SE reservation forces the packet classifier in each node to explicitly select each sender in the list, while a WF allows the packet classifier to simply "wild card" the sender address and port. When there is a large list of senders, a WF style reservation can therefore result in considerably less overhead than an equivalent SE style reservation. For this reason, both SE and WF are included in the protocol.

Other reservation options and styles may be defined in the future.

1.4 Examples of Styles

This section presents examples of each of the reservation styles and shows the effects of merging.

Figure 4 illustrates a router with two incoming interfaces through which data streams will arrive, labeled (a) and (b), and two outgoing interfaces through which data will be forwarded, labeled (c) and (d). This topology will be assumed in the examples that follow. There are three upstream senders; packets from sender S1 (S2 and S3) arrive through previous hop (a) ((b), respectively). There are also three downstream receivers; packets bound for R1 (R2 and R3) are routed via outgoing interface (c) ((d), respectively). We furthermore assume that R2 and R3 arrive via different next hops, e.g., via the two routers D and D' in Figure 9. This illustrates the effect of a non-RSVP cloud or a broadcast LAN on interface (d).

In addition to the connectivity shown in 4, we must also specify the multicast routes within this node. Assume first that data packets from each Si shown in Figure 4 is routed to both outgoing interfaces. Under this assumption, Figures 5, 6, and 7 illustrate Wildcard-Filter, Fixed-Filter, and Shared-Explicit reservations, respectively.



Figure 4: Router Configuration

For simplicity, these examples show flowspecs as one-dimensional multiples of some base resource quantity B. The "Receive" column shows the RSVP reservation requests received over outgoing interfaces (c) and (d), and the "Reserve" column shows the resulting reservation state for each interface. The "Send" column shows the reservation requests that are sent upstream to previous hops (a) and (b). In the "Reserve" column, each box represents one reserved "pipe" on the outgoing link, with the corresponding flow descriptor.

Figure 5, showing the WF style, illustrates the two possible merging situations. Each of the two next hops on interface (d) results in a separate RSVP reservation request, as shown. These two requests are merged into the effective flowspec 3B, which is used to make the reservation on interface (d). To forward the reservation requests upstream, the reservations on the interfaces (c) and (d) are merged; as a result, the larger flowspec 4B is forwarded upstream to each previous hop.

Figure 6 shows Fixed-Filter (FF) style reservations. The flow descriptors for senders S2 and S3,



Figure 5: Wildcard-Filter (WF) Reservation Example

received from outgoing interfaces (c) and (d), are packed into the request forwarded to previous hop (b). On the other hand, the three different flow descriptors for sender S1 are merged into the single request FF(S1{4B}), which is sent to previous hop (a). For each outgoing interface, there is a separate reservation for each source that has been requested, but this reservation is shared among all the receivers that made the request.

Figure 7 shows an example of Shared-Explicit (SE) style reservations. When SE-style reservations are merged, the resulting filter spec is the union of the original filter specs.



Figure 6: Fixed-Filter (FF) Reservation Example



Figure 7: Shared-Explicit (SE) Reservation Example

The three examples just shown assume that data packets from S1, S2, and S3 are routed to both outgoing interfaces. The top part of Figure 8 shows another routing assumption: data packets from S2 and S3 are not forwarded to interface (c), e.g., because the network topology provides a shorter path for these senders towards R1, not traversing this node. The bottom part of Figure 8 shows WF style reservations under this assumption. Since there is no route from (b) to (c), the reservation forwarded out interface (b) considers only the reservation on interface (d).



Router Configuration



Figure 8: WF Reservation Example – Partial Routing

2 RSVP Protocol Mechanisms

2.1 RSVP Messages



Figure 9: Router Using RSVP

Figure 9 illustrates RSVP's model of a router node. Each data stream arrives from a *previous hop* through a corresponding *incoming interface* and departs through one or more *outgoing interface*(s). The same physical interface may act in both the incoming and outgoing roles for different data flows in the same session. Multiple previous hops and/or next hops may be reached through a given physical interface, as a result of the connected network being a shared medium, or the existence of non-RSVP routers in the path to the next RSVP hop (see Section 2.9). An RSVP daemon preserves the next and previous hop addresses in its reservation and path state, respectively.

There are two fundamental RSVP message types: *Resv* and *Path*.

Each receiver host sends RSVP reservation request (*Resv*) messages upstream towards the senders. These reservation messages must follow exactly the reverse of the routes the data packets will use, upstream to all the sender hosts included in the sender selection. *Resv* messages are delivered to the sender hosts themselves so that the hosts can set up appropriate traffic control parameters for the first hop.

Each RSVP sender host transmits RSVP *Path* messages downstream along the uni-/multicast routes provided by the routing protocol(s), following the paths of the data. These *Path* messages store *path state* in each node along the way. This path state includes at least the unicast IP address of the previous hop node, which is used to route the *Resv* messages hop-by-hop in the reverse direction. (In the future, some routing protocols may supply reverse path forwarding information directly, replacing the reverse-routing function of path state).

A *Path* message may carry the following information in addition to the previous hop address:

- Sender Template

  A *Path* message is required to carry a Sender Template, which describes the format of data packets that the sender will originate. This template is in the form of a filter spec that could be used to select this sender's packets from others in the same session on the same link.

  Like a filter spec, the Sender Template is less than fully general at present, specifying only the sender IP address and optionally the UDP/TCP sender port. It assumes the protocol Id specified for the session.

- Sender Tspec

  A *Path* message is required to carry a Sender Tspec, which defines the traffic characteristics of the data stream that the sender will generate. This Tspec is used by traffic control to prevent over-reservation (and perhaps unnecessary Admission Control failure) on upstream links.

- Adspec

  A *Path* message may optionally carry a package of OPWA advertising information, known as an *Adspec*. An Adspec received in a *Path* message is passed to the local traffic control, which returns an updated Adspec; the updated version is then forwarded in *Path* messages sent downstream.

Path messages are sent with the same source and destination addresses as the data, so that they will be routed correctly through non-RSVP clouds (see Section 2.9). On the other hand, *Resv* messages are sent hop-by-hop; each RSVP-speaking node forwards a *Resv* message to the unicast address of a previous RSVP hop.

2.2 Port Usage

At present an RSVP session is defined by the triple: (DestAddress, ProtocolId, DstPort). Here DstPort is a UDP/TCP destination port field (i.e., a 16-bit quantity carried at octet offset +2 in

the transport header). DstPort may be omitted (set to zero) if the ProtocolId specifies a protocol that does not have a destination port field in the format used by UDP and TCP.

RSVP allows any value for ProtocolId. However, end-system implementations of RSVP may know about certain values for this field, and in particular must know about the values for UDP and TCP (17 and 6, respectively). An end system should give an error to an application that either:

- specifies a non-zero DstPort for a protocol that does not have UDP/TCP-like ports, or
- specifies a zero DstPort for a protocol that does have UDP/TCP-like ports.

Filter specs and sender templates specify the pair: (SrcAddress, SrcPort), where SrcPort is a UDP/TCP source port field (i.e., a 16-bit quantity carried at octet offset +0 in the transport header). SrcPort may be omitted (set to zero) in certain cases.

The following rules hold for the use of zero DstPort and/or SrcPort fields in RSVP.

1. Destination ports must be consistent.

   Path state and/or reservation state for the same DestAddress and ProtocolId must have DstPort values that are all zero or all non-zero. Violation of this condition in a node is a "Conflicting Dest Port" error.

2. Destination ports rule.

   If DstPort in a session definition is zero, all SrcPort fields used for that session must also be zero. The assumption here is that the protocol does not have UDP/TCP-like ports. Violation of this condition in a node is a "Conflicting Src Port" error.

3. Source Ports must be consistent.

   A sender host must not send path state both with and without a zero SrcPort. Violation of this condition is an "Ambiguous Path" error.

2.3 Merging Flowspecs

As noted earlier, a single physical interface may receive multiple reservation requests from different next hops for the same session and with the same filter spec, but RSVP should install only one reservation on that interface. The installed reservation should have an effective flowspec that is the "largest" of the flowspecs requested by the different next hops. Similarly, a *Resv* message forwarded to a previous hop should carry a flowspec that is the "largest" of the flowspecs requested by the different next hops (however, in certain cases the "smallest" is taken rather than the largest, see Section 3.4). These cases all represent flowspec merging.

Flowspec merging requires calculation of the "largest" of a set of flowspecs. However, since flowspecs are generally multi-dimensional vectors (they may contain both Tspec and Rspec components, each of which may itself be multi-dimensional), it may not be possible to strictly order two flowspecs. For example, if one request calls for a higher bandwidth and another calls for a tighter delay bound, one is not "larger" than the other. In such a case, instead of taking the larger, RSVP must compute and use a third flowspec that is at least as large as each. Mathematically, RSVP merges flowspecs using the *least upper bound* (LUB) instead of the maximum. Typically, the LUB is calculated by creating a new flowspec whose components are individually either the max or the min of corresponding components of the flowspecs being merged. For example, the LUB of Tspecs defined by token bucket parameters is computed by taking the maximums of the bucket size and the rate parameters. In several cases, the GLB (Greatest Lower Bound) is used instead of the LUB; this simply interchanges max and min operations.

We can now give the complete rules for calculating the effective flowspec (Te, Re) to be installed on an interface. Here Te is the effective Tspec and Re is the effective Rspec. As an example, consider interface (d) in Figure 9.

1. Re is calculated as the largest (using an LUB if necessary) of the Rspecs in *Resv* messages from different next hops (e.g., D and D') but the same outgoing interface (d).
2. All Tspecs that were supplied in *Path* messages from different previous hops (e.g., some or all of A, B, and B' in Figure 9) are summed; call this sum Path_Te.
3. The maximum Tspec supplied in *Resv* messages from different next hops (e.g., D and D') is calculated; call this Resv_Te.
4. Te is the GLB (greatest lower bound) of Path_Te and Resv_Te.

Flowspecs, Tspecs, and Adspecs are opaque to RSVP. Therefore, the last of these steps is actually performed by traffic control. The definition and implementation of the rules for comparing flowspecs, calculating LUBs and GLBs, and summing Tspecs are outside the definition of RSVP [ServTempl95a]. Section 3.10.4 shows generic calls that an RSVP daemon could use for these functions.

2.4 Soft State

RSVP takes a *soft state* approach to managing the reservation state in routers and hosts. RSVP soft state is created and periodically refreshed by *Path* and *Resv* messages. The state is deleted if no matching refresh messages arrive before the expiration of a *cleanup timeout* interval. State may also be deleted by an explicit *teardown* message, described in the next section. At the expiration

of each *refresh timeout* period and after a state change, RSVP scans its state to build and forward *Path* and *Resv* refresh messages to succeeding hops.

Path and *Resv* messages are idempotent. When a route changes, the next *Path* message will initialize the path state on the new route, and future *Resv* messages will establish reservation state there; the state on the now-unused segment of the route will time out. Thus, whether a message is "new" or a "refresh" is determined separately at each node, depending upon the existing state at that node.

RSVP sends its messages as IP datagrams with no reliability enhancement. Periodic transmission of refresh messages by hosts and routers is expected to handle the occasional loss of an RSVP message. If the effective cleanup timeout is set to K times the refresh timeout period, then RSVP can tolerate K-1 successive RSVP packet losses without falsely erasing a reservation. We recommend that the network traffic control mechanism be statically configured to grant some minimal bandwidth for RSVP messages to protect them from congestion losses.

The state maintained by RSVP is dynamic; to change the set of senders Si or to change any QoS request, a host simply starts sending revised *Path* and/or *Resv* messages. The result will be an appropriate adjustment in the RSVP state in all nodes along the path.

In steady state, refreshing is performed hop-by-hop, to allow merging. When the received state differs from the stored state, the stored state is updated. If this update results in modification of state to be forwarded in refresh messages, these refresh messages must be generated and forwarded immediately, so that state changes can be propagated end-to-end without delay. However, propagation of a change stops when and if it reaches a point where merging causes no resulting state change. This minimizes RSVP control traffic due to changes and is essential for scaling to large multicast groups.

State that is received through a particular interface I* should never be forwarded out the same interface. Conversely, state that is forwarded out interface I* must be computed using only state that arrived on interfaces different from I*. A trivial example of this rule is illustrated in Figure 10, which shows a transit router with one sender and one receiver on each interface (and assumes one next/previous hop per interface). Interfaces (a) and (c) serve as both outgoing and incoming interfaces for this session. Both receivers are making wildcard-scope reservations, in which the *Resv* messages are forwarded to all previous hops for senders in the group, with the exception of the next hop from which they came. The result is independent reservations in the two directions.

There is an additional rule governing the forwarding of *Resv* messages: state from *Resv* messages received from outgoing interface Io should be forwarded to incoming interface Ii only if *Path* messages from Ii are forwarded to Io.



Figure 10: Independent Reservations

2.5 Teardown

Upon arrival, RSVP *teardown* messages remove path and reservation state immediately. Although it is not necessary to explicitly tear down an old reservation, we recommend that all end hosts send a teardown request as soon as an application finishes.

There are two types of RSVP teardown message, *PathTear* and *ResvTear*. A *PathTear* message travels towards all receivers downstream from its point of initiation and deletes path state, as well as all dependent reservation state, along the way. An *ResvTear* message deletes reservation state and travels towards all senders upstream from its point of initiation. A *PathTear* (*ResvTear*) message may be conceptualized as a reversed-sense Path message (Resv message, respectively).

A teardown request may be initiated either by an application in an end system (sender or receiver), or by a router as the result of state timeout. Once initiated, a teardown request must be forwarded hop-by-hop without delay. A teardown message deletes the specified state in the node where it is received. As always, this state change will be propagated immediately to the next node, but only if there will be a net change after merging. As a result, an *ResvTear* message will prune the reservation state back (only) as far as possible.

Like all other RSVP messages, teardown requests are not delivered reliably. The loss of a teardown

request message will not cause a protocol failure because the unused state will eventually time out even though it is not explicitly deleted. If a teardown message is lost, the router that failed to receive that message will time out its state and initiate a new teardown message beyond the loss point. Assuming that RSVP message loss probability is small, the longest time to delete state will seldom exceed one refresh timeout period.

2.6 Errors

There are two RSVP error messages, *ResvErr* and *PathErr*. *PathErr* messages are very simple. They are simply sent upstream to the sender that created the error, and they do not change path state in the nodes though which they pass. There are only a few possible causes of path errors.

However, there are a number of ways for a syntactically valid reservation request to fail at some node along the path, for example:

1. The effective flowspec that is computed using the new request may fail admission control.
2. Administrative policy may prevent the requested reservation.
3. There may be no matching path state, so that the request cannot be forwarded towards the sender(s).
4. A reservation style that requires the explicit selection of a unique sender may have a filter spec that is ambiguous, i.e., that matches more than one sender in the path state, due to the use of wildcard fields in the filter spec.
5. The requested style may be incompatible with the style(s) of existing reservations. The incompatibility may occur among reservations for the same session on the same outgoing interface, or among effective reservations on different outgoing interfaces.

A node may also decide to preempt an established reservation.

The handling of *ResvErr* messages is somewhat complex (Section 3.4). Since a request that fails may be the result of merging a number of requests, a reservation error must be reported to all of the responsible receivers. In addition, merging heterogeneous requests creates a potential difficulty known as the "killer reservation" problem, in which one request could deny service to another. There are actually two killer-reservation problems.

1. The first killer reservation problem (KR-I) arises when there is already a reservation Q0 in place. If another receiver now makes a larger reservation Q1 > Q0, the result of merging Q0

and Q1 may be rejected by admission control in some upstream node. This must not deny service to Q0.

The solution to this problem is simple: when admission control fails for a reservation request, any existing reservation is left in place.

2. The second killer reservation problem (KR-II) is the converse: the receiver making a reservation Q1 is persistent even though Admission Control is failing for Q1 in some node. This must not prevent a different receiver from now establishing a smaller reservation Q0 that will succeed.

   To solve this problem, a *ResvErr* message establishes additional state, called *blockade state*, in each node through which it passes. Blockade state in a node modifies the merging procedure to omit the offending flowspec (Q1 in the example) from the merge, allowing a smaller request to be forwarded and established. The Q1 reservation state is said to be *blockaded*. Detailed rules are presented in Section 3.4.

A reservation request that fails Admission Control creates blockade state but is left in place in nodes downstream of the failure point. It has been suggested that these reservations downstream from the failure represent "wasted" reservations and should be timed out if not actively deleted. However, in general the downstream reservations will not be "wasted".

- There are two possible reasons for a receiver persisting in a failed reservation: (1) it is polling for resource availability along the entire path, or (2) it wants to obtain the desired QoS along as much of the path as possible. Certainly in the second case, and perhaps in the first case, the receiver will want to hold onto the reservations it has made downstream from the failure.
- If these downstream reservations were not retained, the responsiveness of RSVP to certain transient failures would be impaired. For example, suppose a route "flaps" to an alternate route that is congested, so an existing reservation suddenly fails, then quickly recovers to the original route. The blockade state in each downstream router must not remove the state or prevent its immediate refresh.
- If we did not refresh the downstream reservations, they might time out, to be restored every Td seconds. Such on/off behavior might be very distressing for users.

2.7 Confirmation

To request a confirmation for its reservation request, a receiver Rj includes in the *Resv* message a confirmation-request object containing Rj's IP address. At each merge point, only the largest flowspec and any accompanying confirmation-request object is forwarded upstream. If the reservation request from Rj is equal to or smaller than the reservation in place on a node, its *Resv* are not

forwarded further, and if the *Resv* included a confirmation-request object, a *ResvConf* message is sent back to Rj. This mechanism has the following consequences:

- A new reservation request with a flowspec larger than any in place for a session will normally result in either a *ResvErr* or a *ResvConf* message back to the receiver from each sender. In this case, the *ResvConf* message will be an end-to-end confirmation.
- The receipt of a *ResvConf* gives no guarantees. Assume the first two reservation requests from receivers R1 and R2 arrive at the node where they are merged. R2, whose reservation was the second to arrive at that node, may receive a *ResvConf* from that node while R1's request has not yet propagated all the way to a matching sender and may still fail. Thus, R2 may receive a *ResvConf* although there is no end-to-end reservation in place; furthermore, R2 may receive a *ResvConf* followed by a *ResvErr*.

2.8 Policy and Security

RSVP-mediated QoS requests will result in particular user(s) getting preferential access to network resources. To prevent abuse, some form of back pressure on users is likely to be required. This back pressure might take the form of administrative rules, or of some form of real or virtual billing for the "cost" of a reservation. The form and contents of such back pressure is a matter of administrative policy that may be determined independently by each administrative domain in the Internet.

Therefore, there will be policy control as well as admission control over the establishment of reservations. As input to policy control, RSVP messages may carry policy data. Policy data may include credentials identifying users or user classes, account numbers, limits, quotas, etc. Like flowspecs, policy data will be opaque to RSVP, which will simply pass it to a *Local Policy Module* (LPM) for a decision.

To protect the integrity of the policy control mechanisms, it may be necessary to ensure the integrity of RSVP messages against corruption or spoofing, hop by hop. For this purpose, RSVP messages may carry integrity objects that can be created and verified by neighbor RSVP-capable nodes. These objects use a keyed cryptographic digest technique and assume that RSVP neighbors share a secret [Baker96].

User policy data in reservation request messages presents a scaling problem. When a multicast group has a large number of receivers, it will be impossible or undesirable to carry all receivers' policy data upstream to the sender(s). The policy data will have to be administratively merged at places near the receivers, to avoid excessive policy data. Administrative merging implies checking the user credentials and accounting data and then substituting a token indicating the check has succeeded. A chain of trust established using integrity fields will allow upstream nodes to accept

these tokens.

In summary, different administrative domains in the Internet may have different policies regarding their resource usage and reservation. The role of RSVP is to carry policy data associated with each reservation to the network as needed. Note that the merge points for policy data are likely to be at the boundaries of administrative domains. It may be necessary to carry accumulated and unmerged policy data upstream through multiple nodes before reaching one of these merge points.

This document does not specify the contents of policy data, the structure of an LPM, or any generic policy models. These will be defined in the future.

2.9 Automatic RSVP Tunneling

It is impossible to deploy RSVP (or any new protocol) at the same moment throughout the entire Internet. Furthermore, RSVP may never be deployed everywhere. RSVP must therefore provide correct protocol operation even when two RSVP-capable routers are joined by an arbitrary "cloud" of non-RSVP routers. Of course, an intermediate cloud that does not support RSVP is unable to perform resource reservation. However, if such a cloud has sufficient capacity, it may still provide acceptable realtime service.

RSVP automatically tunnels through such a non-RSVP cloud. Both RSVP and non-RSVP routers forward *Path* messages towards the destination address using their local uni-/multicast routing table. Therefore, the routing of *Path* messages will be unaffected by non-RSVP routers in the path. When a *Path* message traverses a non-RSVP cloud, it carries to the next RSVP-capable node the IP address of the last RSVP-capable router before entering the cloud. This effectively constructs a tunnel through the cloud for *Resv* messages, which can then be forwarded directly to the next RSVP-capable router on the path(s) back towards the source.

Even though RSVP operates correctly through a non-RSVP cloud, the non-RSVP-capable nodes will in general perturb the QoS provided to a receiver. Therefore, RSVP tries to inform the receiver when there are non-RSVP-capable hops in the path to a given sender, by means of two flag bits in the SESSION object of a *Path* message; see Section 3.7 and Appendix A.

Some topologies of RSVP routers and non-RSVP routers can cause *Resv* messages to arrive at the wrong RSVP-capable node, or to arrive at the wrong interface of the correct node. An RSVP daemon must be prepared to handle either situation. If the destination address does not match any local interface and the message is not a *Path* or *PathTear* the message must be forwarded without further processing by this node. When a *Resv* message does arrive at the addessed node, the IP destination address (or the LIH, defined later) must be used to determine the interface to receive the reservation.

2.10 Host Model

Before a session can be created, the session identification, comprised of DestAddress and perhaps the generalized destination port, must be assigned and communicated to all the senders and receivers by some out-of-band mechanism. When an RSVP session is being set up, the following events happen at the end systems.

H1 A receiver joins the multicast group specified by DestAddress, using IGMP.

H2 A potential sender starts sending RSVP *Path* messages to the DestAddress.

H3 A receiver application receives a *Path* message.

H4 A receiver starts sending appropriate *Resv* messages, specifying the desired flow descriptors.

H5 A sender application receives a *Resv* message.

H6 A sender starts sending data packets.

There are several synchronization considerations.

- H1 and H2 may happen in either order.
- Suppose that a new sender starts sending data (H6) but there are no multicast routes because no receivers have joined the group (H1). Then the data will be dropped at some router node (which node depends upon the routing protocol) until receivers(s) appear.
- Suppose that a new sender starts sending *Path* messages (H2) and data (H6) simultaneously, and there are receivers but no *Resv* messages have reached the sender yet (e.g., because its *Path* messages have not yet propagated to the receiver(s)). Then the initial data may arrive at receivers without the desired QoS. The sender could mitigate this problem by awaiting arrival of the first *Resv* message (H5); however, receivers that are farther away may not have reservations in place yet.
- If a receiver starts sending *Resv* messages (H4) before receiving any *Path* messages (H3), RSVP will return error messages to the receiver.

  The receiver may simply choose to ignore such error messages, or it may avoid them by waiting for *Path* messages before sending *Resv* messages.

A specific application program interface (API) for RSVP is not defined in this protocol spec, as it may be host system dependent. However, Section 3.10.1 discusses the general requirements and outlines a generic interface.

3 RSVP Functional Specification

3.1 RSVP Message Formats

An RSVP message or message fragment consists of a common header, an optional integrity-check data structure, and a body consisting of a variable number of variable-length, typed *objects*. The integrity-check data structure is itself an object, of class INTEGRITY [Baker96]. In a fragmented message, INTEGRITY objects must occur either in every fragment or else in no fragment. Fragmentation of a message allows division of an object across two (or more) successive fragments.

The following subsections define the formats of the common header, the object structures, and each of the RSVP message types. For each RSVP message type, there is a set of rules for the permissible choice of object types. These rules are specified using Backus-Naur Form (BNF) augmented with square brackets surrounding optional sub-sequences. The BNF implies an order for the objects in a message. However, in many (but not all) cases, object order makes no logical difference. An implementation should create messages with the objects in the order shown here, but accept the objects in any order except where the order is logically required (as noted in the following).

3.1.1 Common Header



The fields in the common header are as follows:

Vers: 4 bits

Protocol version number. This is version 1.

Flags: 4 bits

0x01 = INTEGRITY object present

This flag indicates that an INTEGRITY object follows immediately after the common header. The use of the INTEGRITY object is described in [Baker96].

0x02-0x80: Reserved

Type: 8 bits

1 = *Path*
2 = *Resv*
3 = *PathErr*
4 = *ResvErr*
5 = *PathTear*
6 = *ResvTear*
7 = *ResvConf*

RSVP Checksum: 16 bits

The one's complement of the one's complement sum of the message (fragment), with the checksum field replaced by zero for the purpose of computing the checksum. An all-zero value means that no checksum was transmitted.

RSVP Length: 16 bits

The total length of this RSVP packet in bytes, including the common header and the variable-length objects that follow. If the MF flag is on or the Fragment Offset field is non-zero, this will generally differ from the length of the current fragment.

Send_TTL: 8 bits

The IP TTL value with which the message was sent.

Message ID: 32 bits

An unique identifying value that is used to identify and reassemble the fragments of a single message. It is assigned to the RSVP message by the node whose address is the IP source address of the message (fragment).

MF: More Fragments Flag: 1 bit

This flag is the low-order bit of a byte; the seven high-order bits are reserved. It is on for all but the last fragment of a message.

Fragment Offset: 24 bits

This field gives the byte offset of the current fragment in the complete message.

For a *Path* or *PathTear* message, the Message Id is assigned by the sender host, and it must be copied at each successive node into forwarded messages. For other messages, it is assigned at the

most recent RSVP hop to forward the message. When a message is fragmented, the Messsage Id must be copied into each fragment. When a fragmented packet is received, it may be reassembled by RSVP out of fragments carrying the same Message Id and IP source address.

RSVP messages that exceed the MTU of the interface on which they are being sent must be split into fragments, each of which will fit into an MTU.

3.1.2 Object Formats

Every object consists of one or more 32-bit words with a one-word header, in the following format:



An object header has the following fields:

Length

A 16-bit field containing the total object length in bytes. Must always be a multiple of 4, and at least 4.

Class-Num

Identifies the object class; values of this field are defined in Appendix A. Each object class has a name, which is always capitalized in this document. An RSVP implementation must recognize the following classes:

NULL

A NULL object has a Class-Num of zero, and its C-Type is ignored. Its length must be at least 4, but can be any multiple of 4. A NULL object may appear anywhere in a sequence of objects, and its contents will be ignored by the receiver.

SESSION

Contains the IP destination address (DestAddress), the IP protocol id, and a generalized destination port, to define a specific session for the other objects that follow. Required in every RSVP message.

RSVP_HOP

Carries the IP address of the RSVP-capable node that sent this message. This document refers to a RSVP_HOP object as a PHOP (*previous hop*) object for downstream messages or as a NHOP (*next hop*) object for upstream messages.

TIME_VALUES

Contains the value for the refresh period R used by the creator of the message; see 3.6. Required in every *Path* and *Resv* message.

STYLE

Defines the reservation style plus style-specific information that is not in FLOWSPEC or FILTER_SPEC objects. Required in every *Resv* message.

FLOWSPEC

Defines a desired QoS, in a *Resv* message.

FILTER_SPEC

Defines a subset of session data packets that should receive the desired QoS (specified by an FLOWSPEC object), in a *Resv* message.

SENDER_TEMPLATE

Contains a sender IP address and perhaps some additional demultiplexing information to identify a sender, in a *Path* message.

SENDER_TSPEC

Defines the traffic characteristics of a sender's data stream, in a *Path* message.

ADSPEC

Carries OPWA data, in a *Path* message.

ERROR_SPEC

Specifies an error, in a *PathErr* or *ResvErr* message.

POLICY_DATA

Carries information that will allow a local policy module to decide whether an associated reservation is administratively permitted. May appear in *Path*, *Resv*, *PathErr*, or *ResvErr* message.

INTEGRITY

Contains cryptographic data to authenticate the originating node and to verify the contents of this RSVP message. See [Baker96].

SCOPE

An explicit list of sender hosts towards which to forward a message. May appear in a *Resv ResvErr* or *ResvTear* message.

RESV_CONFIRM

Carries the IP address of a receiver that requested a confirmation. May appear in a *Resv* or *ResvConf* message.

C-Type

Object type, unique within Class-Num. Values are defined in Appendix A.

The maximum object content length is 65528 bytes. The Class-Num and C-Type fields may be used together as a 16-bit number to define a unique type for each object.

The high-order two bits of the Class-Num is used to determine what action a node should take if it does not recognize the Class-Num of an object; see Section 3.9.

3.1.3 Path Messages

Each sender host periodically sends a *Path* message containing a description of each data stream it originates. The *Path* message travels from a sender to receiver(s) along the same path(s) used by the data packets. The IP source address of a *Path* message is an address of the sender it describes, while the destination address is the DestAddress for the session. These addresses assure that the message will be correctly routed through a non-RSVP cloud.

Each RSVP-capable node along the path(s) captures *Path* messages and processes them to build local path state. The node then forwards the *Path* messages towards the receiver(s), replicating it as dictated by multicast routing, while preserving the original IP source address. *Path* messages eventually reach the applications on all receivers; however, they are not looped back to a receiver running in the same application process as the sender.

The format of a *Path* message is as follows:

```
<Path Message> ::= <Common Header> [ <INTEGRITY> ]

                            <SESSION> <RSVP_HOP>

                            <TIME_VALUES>

                            [ <POLICY_DATA> ... ]

                            <sender descriptor>

<sender descriptor> ::= <SENDER_TEMPLATE> <SENDER_TSPEC>

                          [ <ADSPEC> ]
```

If the INTEGRITY object is present, there must be an INTEGRITY object immediately following the common header in every fragment of the message, in this and all other messages. There are no other requirements on transmission order, although the above order is recommended. Any number of POLICY_DATA objects may appear.

The PHOP (i.e., the RSVP_HOP) object of each *Path* message contains the address of the interface through which the *Path* message was most recently sent. The SENDER_TEMPLATE object defines the format of data packets from this sender, while the SENDER_TSPEC object specifies the traffic characteristics of the flow. Optionally, there may be an ADSPEC object carrying advertising (OPWA) data.

A *Path* message received at a node is processed to create path state for the sender defined by the SENDER_TEMPLATE and SESSION objects. Any POLICY_DATA, SENDER_TSPEC, and ADSPEC objects are also saved in the path state. If an error is encountered while processing a *Path* message, a *PathErr* message is sent to the originating sender of the *Path* message. *Path* messages must satisfy the rules on SrcPort and DstPort in Section 2.2.

Periodically, the RSVP daemon at a node scans the path state to create new *Path* messages to forward downstream. Each message contains a **sender descriptor** defining one sender. The RSVP daemon forwards these messages using routing information it obtains from the appropriate uni-/multicast routing daemon. The route depends upon the session DestAddress, and for some routing protocols also upon the source (sender's IP) address. The routing information generally includes the list of none or more outgoing interfaces to which the *Path* message to be forwarded. Because each outgoing interface has a different IP address, the *Path* messages sent out different interfaces contain different PHOP addresses. In addition, ADSPEC objects carried in *Path* messages will also generally differ for different outgoing interfaces.

Some IP multicast routing protocols (e.g., DVMRP, PIM, and MOSPF) also keep track of the expected incoming interface for each source host to a multicast group. Whenever this information is available, RSVP should check the incoming interface of each *Path* message and immediately discard those messages that have arrived on the wrong interface.

3.1.4 Resv Messages

Resv messages carry reservation requests hop-by-hop from receivers to senders, along the reverse paths of data flows for the session. The IP destination address of a *Resv* message is the unicast address of a previous-hop node, obtained from the path state. The IP source address is an address of the node that sent the message.

The *Resv* message format is as follows:

```
<Resv Message> ::= <Common Header> [ <INTEGRITY> ]

                         <SESSION>  <RSVP_HOP>

                         <TIME_VALUES>

                         [ <POLICY_DATA> ... ]

                         [ <RESV_CONFIRM> ]  [ <SCOPE> ]

                         <STYLE> <flow descriptor list>

<flow descriptor list> ::=  <flow descriptor> |

                 <flow descriptor list> <flow descriptor>
```

The NHOP (i.e., the RSVP_HOP) object contains the IP address of the interface through which the *Resv* message was sent. The appearance of a RESV_CONFIRM object signals a request for a reservation confirmation and carries the IP address of the receiver to which the *ResvConf* should be sent. Any number of POLICY_DATA objects may appear.

The STYLE object followed by the **flow descriptor list** must occur at the end of the message. There are no other requirements on transmission order, although the above order is recommended.

The BNF above defines a **flow descriptor list** as simply a list of **flow descriptor**s. The following style-dependent rules specify in more detail the composition of a valid **flow descriptor list** for each of the reservation styles; the order shown must be used.

- WF Style:

  ```
  <flow descriptor list> ::=  <WF flow descriptor>

  <WF flow descriptor> ::= <FLOWSPEC>
  ```

- FF style:

  ```
  <flow descriptor list> ::=

            <FLOWSPEC>  <FILTER_SPEC>  |
  ```

```
            <flow descriptor list> <FF flow descriptor>

    <FF flow descriptor> ::=

            [ <FLOWSPEC> ] <FILTER_SPEC>
```

Each elementary FF style request is defined by a single (FLOWSPEC, FILTER_SPEC) pair, and multiple such requests may be packed into the **flow descriptor list** of a single *Resv* message. A FLOWSPEC object can be omitted if it is identical to the most recent such object that appeared in the list; the first **FF flow descriptor** must contain a FLOWSPEC.

Each **flow descriptor** in the list must be processed independently, and a separate *ResvErr* message must be generated for each one that is in error.

- SE style:

```
<flow descriptor list> ::= <SE flow descriptor>

<SE flow descriptor> ::=

                        <FLOWSPEC> <filter spec list>

<filter spec list> ::=  <FILTER_SPEC>

                    |   <filter spec list> <FILTER_SPEC>
```

The reservation scope, i.e., the set of senders towards which a particular reservation is to be forwarded, is determined as follows:

- Explicit sender selection

  Select a particular sender by matching each FILTER_SPEC object against the path state created from SENDER_TEMPLATE objects. An ambiguous match, i.e., a FILTER_SPEC matching more than one SENDER_TEMPLATE (e.g. through use of a wildcard port), is an error.

- Wildcard sender selection

  All senders that route to the given outgoing interface match this request. A SCOPE object, if present, contains an explicit list of sender IP addresses. If there is no SCOPE object, the scope is determined by the relevant set of senders in the path state.

  Whenever a *Resv* message with wildcard sender selection is forwarded to more than one previous hop, a SCOPE object must be included in the message. See Section 3.3 below.

3.1.5 Teardown Messages

There are two types of RSVP Teardown message, *PathTear* and *ResvTear*.

- A *PathTear* message deletes path state (which in turn deletes any reservation state for that sender) and travels towards all receivers that are downstream from the initiating node. A *PathTear* message is routed like a *Path* message, and its IP destination address is DestAddress for the session.
- A *ResvTear* message deletes reservation state and travels towards all matching senders upstream from the initiating node. A *ResvTear* message is routed in the same way as a corresponding *Resv* message, and its IP destination address is the unicast address of a previous hop.

```
<PathTear Message> ::= <Common Header> [<INTEGRITY>]

                            <SESSION> <RSVP_HOP>

                            <sender descriptor>

<sender descriptor> ::= (see earlier definition)

<ResvTear Message> ::= <Common Header> [<INTEGRITY>]

                            <SESSION> <RSVP_HOP>

                            [ <SCOPE> ] <STYLE>

                            <flow descriptor list>

<flow descriptor list> ::= (see earlier definition)
```

FLOWSPEC objects in the **flow descriptor list** of a *ResvTear* message will be ignored and may be omitted. The order requirements for **sender descriptor**, STYLE object, and **flow descriptor list** are as given earlier for *Path* and *Resv* messages.

Note that, unless it is accidentally dropped along the way, a *PathTear* message will reach all receivers down stream from its origination. On the other hand, a *ResvTear* message will cease to be forwarded at the same node where merging suppresses forwarding of the corresponding *Resv* messages. In each node N along the way, if the *ResvTear* message causes the removal of all state for this session, N will create a new teardown message to be propagated further upstream; otherwise,

the *ResvTear* message may result in the immediate forwarding of a modified *Resv* refresh message.

Deletion of path state as the result of a *PathTear* message or a timeout must cause any adjustments in related reservation state required to maintain consistency in the local node. The adjustment in reservation state depends upon the style. For example, suppose a *PathTear* deletes the path state for a sender S. If the style specifies explicit sender selection (FF or SE), any reservation with a filter spec matching S should be deleted; if the style has wildcard sender selection (WF), the reservation should be deleted if S is the last sender to the session. These reservation changes should not trigger an immediate *Resv* refresh message, since the *PathTear* message have already made the required changes upstream. However, at the node in which a *ResvTear* message stops, the change of reservation state may trigger a *Resv* refresh starting at that node.

3.1.6 Error Messages

There are two types of RSVP error messages.

- *PathErr* messages result from *Path* messages and travel upstream towards the senders. *PathErr* messages are routed hop-by-hop using the path state; at each hop, the IP destination address is the unicast address of a previous hop. *PathErr* messages do not modify the state of any node through which they pass; instead, they are only reported to the sender application.
- *ResvErr* messages result from *Resv* messages and travel downstream towards the appropriate receivers. They are routed hop-by-hop using the reservation state; at each hop, the IP destination address is the unicast address of a next-hop node.

An error encountered while processing an error message must cause the error message to be discarded without creating further error messages; however, logging of such events may be useful.

```
<PathErr message> ::= <Common Header> [ <INTEGRITY> ]

                          <SESSION> <ERROR_SPEC>

                          [ <POLICY_DATA> ...]

                          <sender descriptor>

<sender descriptor> ::= (see earlier definition)
```

```
<ResvErr Message> ::= <Common Header> [ <INTEGRITY> ]

                              <SESSION> <ERROR_SPEC>

                              [ <POLICY_DATA> ...]

                              [ <SCOPE> ]

                             <STYLE> <error flow descriptor>
```

The ERROR_SPEC object specifies the error and includes the IP address of the node that detected the error (Error Node Address). One or more POLICY_DATA objects may be included in an error message to provide relevant information (i.e., when an administrative failure is being reported). The STYLE object is copied from the *Resv* message in error. The use of the SCOPE object in a *ResvErr* message is defined below in Section 3.3.

The following style-dependent rules define the composition of a valid **error flow descriptor**; the object order requirements are as given earlier for a *Resv* message.

- WF Style:

  ```
  <error flow descriptor> ::= <WF flow descriptor>
  ```

- FF style:

  ```
  <error flow descriptor> ::= <FF flow descriptor>
  ```

- SE style:

  ```
  <error flow descriptor> ::= <SE flow descriptor>
  ```

Note that a *ResvErr* message contains only one flow descriptor. Therefore, a *Resv* message that contains N $>$ 1 flow descriptors (FF style) may create up to N separate *ResvErr* messages.

Generally speaking, a *ResvErr* message should be forwarded towards all receivers that may have caused the error being reported. More specifically:

- The node that detects an error in a reservation request sends a *ResvErr* message to the next hop from which the erroneous reservation came.

This message must contain the information required to define the error and to route the error message in later hops. It therefore includes an ERROR_SPEC object, a copy of the STYLE object, and the appropriate **error flow descriptor**. If the error is an admission control failure, any reservation already in place will be left in place, and the InPlace flag bit must be on in the ERROR_SPEC of the *ResvErr* message.

- Succeeding nodes forward the *ResvErr* message to next hops that have local reservation state. For reservations with wildcard scope, there is an additional limitation on forwarding *ResvErr* messages, to avoid loops; see Section 3.3. There is also a rule restricting the forwarding of *Resv* messages for Admission Control failures; see Section 3.4.

  A *ResvErr* message that is forwarded should carry the FILTER_SPEC from the corresponding reservation state.

- When a *ResvErr* message reaches a receiver, the STYLE object, **flow descriptor list**, and ERROR_SPEC object (including its flags) should be delivered to the receiver application.

3.1.7 Confirmation Messages

ResvConf messages are sent to (probabilistically) acknowledge reservation requests. A *ResvConf* message is sent as the result of the appearance of a RESV_CONFIRM object in a *Resv* message.

A *ResvConf* message is sent to the unicast address of a receiver host; the address is obtained from the RESV_CONFIRM object. However, a *ResvConf* message is forwarded to the receiver hop-by-hop, to accommodate the hop-by-hop integrity check mechanism.

```
<ResvConf Message> ::= <Common Header> <SESSION>

                       <ERROR_SPEC>

                       <RESV_CONFIRM>

                       <STYLE> <flow descriptor list>

<flow descriptor list> ::= (see earlier definition)
```

The RESV_CONFIRM object is a copy of that object in the *Resv* message that triggered the confirmation. The ERROR_SPEC is used only to carry the IP address of the originating node, in the Error Node Address; the Error Code and Value are zero to indicate a confirmation. The **flow descriptor list** specifies the particular reservations that are being confirmed; it may be a subset of **flow descriptor list** of the *Resv* that requested the confirmation.

The object order requirements within the **flow descriptor list** are the same as those given earlier for a *Resv* message.

3.2 Sending RSVP Messages

RSVP messages are sent hop-by-hop between RSVP-capable routers as "raw" IP packets with protocol number 46. Raw IP packets are intended to be used between an end system and the first/last hop router, although it is also possible to encapsulate RSVP messages as UDP datagrams for end-system communication, as described in Appendix C. UDP encapsulation is needed for systems that cannot do raw network I/O.

Path, *PathTear*, and *ResvConf* messages must be sent with the Router Alert IP option [Katz95] in their IP headers. This option may be used in the fast forwarding path of a high-speed router to detect datagrams that require special processing.

Upon the arrival of an RSVP message M that changes the state, a node must forward the modified state immediately. However, this must not trigger sending an message out the interface through which M arrived (as could happen if the implementation simply triggered an immediate refresh of all state for the session). This rule is necessary to prevent packet storms on broadcast LANs.

An RSVP message must be fragmented when necessary to fit into the MTU of the interface through which it will be sent. All fragments of the message should carry the same unique value of the Message ID field, as well as appropriate Fragment Offset and MF bits, in their common headers. When an RSVP message arrives, it must be reassembled before it can be processed. The refresh period R can be used as an appropriate reassembly timeout time.

Between adjacent RSVP-capable routers, RSVP-level fragmentation mechanism should normally be used in lieu of fragmentation at the IP level. However, IP-level fragmentation may still occur when RSVP messages travel through a non-RSVP cloud. In case of IP6, which does not support IP fragmentation at routers, an RSVP implementation must use Path MTU Discovery or hand configuration to obtain an appropriate MTU between adjacent RSVP neighbors.

RSVP uses its periodic refresh mechanisms to recover from occasional packet losses. Under network overload, however, substantial losses of RSVP messages could cause a failure of resource reservations. To control the queueing delay and dropping of RSVP packets, routers should be configured to offer them a preferred class of service. If RSVP packets experience noticeable losses when crossing a congested non-RSVP cloud, a larger value can be used for the timeout factor K (see section 3.6 below).

Some multicast routing protocols provide for *multicast tunnels*, which encapsulate multicast packets

for transmission through routers that do not have multicast capability. A multicast tunnel looks like a logical outgoing interface that is mapped into some physical interface. A multicast routing protocol that supports tunnels will describe a route using a list of logical rather than physical interfaces. RSVP can run through multicast tunnels in the following manner:

1. When a node N forwards a *Path* message out a logical outgoing interface L, it includes in the message some encoding of the identity of L, called the *logical interface handle* or LIH. The LIH value is carried in the RSVP_HOP object.
2. The next hop node N' stores the LIH value in its path state.
3. When N' sends a *Resv* message to N, it includes the LIH value from the path state (again, in the RSVP_HOP object).
4. When the *Resv* message arrives at N, its LIH value provides the information necessary to attach the reservation to the appropriate logical interface. Note that N creates and interprets the LIH; it is an opaque value to N'.

3.3 Avoiding RSVP Message Loops

Forwarding of RSVP messages must avoid looping. In steady state, *Path* and *Resv* messages are forwarded only once per refresh period on each hop. This avoids looping packets, but there is still the possibility of an *auto-refresh* loop, clocked by the refresh period. Such auto-refresh loops keep state active "forever", even if the end nodes have ceased refreshing it, until either the receivers leave the multicast group and/or the senders stop sending *Path* messages. On the other hand, error and teardown messages are forwarded immediately and are therefore subject to looping.

Consider each message type.

- *Path* Messages

  Path messages are forwarded in exactly the same way as IP data packets. Therefore there should be no loops of *Path* messages, even in a topology with cycles.

- *PathTear* Messages

  PathTear messages use the same routing as *Path* messages and therefore cannot loop.

- *PathErr* Messages

  Since *Path* messages do not loop, they create path state defining a loop-free reverse path to each sender. *PathErr* messages are always directed to particular senders and therefore cannot loop.

- *Resv* Messages

  Resv messages directed to particular senders (i.e., with explicit sender selection) cannot loop. However, *Resv* messages with wildcard sender selection (WF style) have a potential for auto-refresh looping.

- *ResvTear* Messages

  Although *ResvTear* messages are routed the same as *Resv* messages, during the second pass around a loop there will be no state so any *ResvTear* message will be dropped. Hence there is no looping problem here.

- *ResvErr* Messages

  ResvErr messages for WF style reservations may loop for essentially the same reasons that *Resv* messages loop.

- *ResvConf* Messages

  ResvConf messages are forwarded towards a fixed unicast receiver address and cannot loop.

If the topology has no loops, then looping of *Resv* and *ResvErr* messages with wildcard sender selection can be avoided by simply enforcing the rule given earlier: state that is received through a particular interface must never be forwarded out the same interface. However, when the topology does have cycles, further effort is needed to prevent auto-refresh loops of wildcard *Resv* messages and fast loops of wildcard *ResvErr* messages. The solution to this problem adopted by this protocol specification is for such messages to carry an explicit sender address list in a SCOPE object.

When a *Resv* message with WF style is to be forwarded to a particular previous hop, a new SCOPE object is computed from the SCOPE objects that were received in matching *Resv* messages. If the computed SCOPE object is empty, the message is not forwarded to the previous hop; otherwise, the message is sent containing the new SCOPE object. The rules for computing a new SCOPE object for a *Resv* message are as follows:

1. The union is formed of the sets of sender IP addresses listed in all SCOPE objects in the reservation state for the given session.

   If reservation state from some NHOP does not contain a SCOPE object, a substitute sender list must be created and included in the union. For a message that arrived on outgoing interface OI, the substitute list is the set of senders that route to OI.

2. Any local senders (i.e., any sender applications on this node) are removed from this set.
3. If the SCOPE object is to be sent to PHOP, remove from the set any senders that did not come from PHOP.



Figure 11: SCOPE Objects in Wildcard-Scope Reservations

Figure 11 shows an example of wildcard-scoped (WF style) *Resv* messages. The address lists within SCOPE objects are shown in square brackets. Note that there may be additional connections among the nodes, creating looping topology that is not shown.

SCOPE objects are not necessary if the multicast routing uses shared trees or if the reservation style has explicit sender selection. Furthermore, attaching a SCOPE object to a reservation may be deferred to a node which has more than one previous hop upstream.

The following rules are used for SCOPE objects in *ResvErr* messages with WF style:

1. The node that detected the error initiates an *ResvErr* message containing a copy of the SCOPE object associated with the reservation state or message in error.
2. Suppose a wildcard-scoped *ResvErr* message arrives at a node with a SCOPE object contain-

ing the sender host address list L. The node forwards the *ResvErr* message using the rules of Section 3.1.6. However, the *ResvErr* message forwarded out OI must contain a SCOPE object derived from L by including only those senders that route to OI. If this SCOPE object is empty, the *ResvErr* message should not be sent out OI.

3.4 Blockade State

The basic rule for creating a *Resv* refresh message is to merge the flowspecs of the reservation requests in place in the node, by computing their LUB. However, this rule is modified by the existence of *blockade state* resulting from *ResvErr* messages, to solve the KR-II problem (Section 2.6). The blockade state also enters into the routing of *ResvErr* messages for Admission Control failure.

When a *ResvErr* message for an Admission Control failure is received, its flowspec Qe is used to create or refresh an element of local blockade state. Each element of blockade state consists of a blockade flowspec Qb taken from the flowspec of the last *ResvErr* and an associated blockade timer Tb. When the blockade timer expires, the blockade state is deleted.

The granularity of blockade state depends upon the style of the *ResvErr* message that created it. For an explicit style, there may be a blockade state element (Qb(S),Tb(S)) for each sender S. For a wildcard style, blockade state is per previous hop P.

An element of blockade state with flowspec Qb is said to "blockade" a reservation with flowspec Qi if Qb is not (strictly) greater than Qi. For example, suppose that the LUB of two flowspecs is computed by taking the max of each of their corresponding components. Then Qb blockades Qi if for some component j, Qb[j] <= Qi[j].

Suppose that a node receives a *ResvErr* message from previous hop P (or, if style is explicit, sender S) as the result of an Admission Control failure upstream. Then:

1. An element of blockade state is created for P (or S) if it did not exist.
2. Qb(P) (or Qb(S)) is set equal to the flowspec Qe from the *ResvErr* message.
3. A corresponding blockade timer Tb(P) (or Tb(S)) is started or restarted for a time Kb*R. Here Kb is a fixed multiplier and R is the refresh interval for reservation state. Kb should be configurable.
4. If there is some local reservation state that is not blockaded (see below), an immediate reservation refresh for P (or S) is generated.
5. The *ResvErr* message is forwarded to next hops in the following way. If the InPlace bit is off, the *ResvErr* message is forwarded to all next hops for which there is reservation state. If

the InPlace bit is on, the *ResvErr* message is forwarded only to the next hops whose Qi is blockaded by Qb.

Finally, we present the modified rule for merging flowspecs to create a reservation refresh message.

- If there are any local reservation requests Qi that are not blockaded, these are merged by computing their LUB. The blockaded reservations are ignored; this allows forwarding of a smaller reservation that has not failed and may perhaps succeed, after a larger reservation fails.
- Otherwise (all local requests Qi are blockaded), they are merged by taking the GLB (Greatest Lower Bound) of the Qi's.

This refresh merging algorithm is applied separately to each flow (each sender or PHOP) contributing to a shared reservation (WF or SE style).

Figure 12 shows an example of the the application of blockade state for a shared reservation (WF style). There are two previous hops labelled (a) and (b), and two next hops labelled (c) and (d). The larger reservation 4B arrived from (c) first, but it failed somewhere upstream via PHOP (a), but not via PHOP (b). The figures show the final "steady state" after the smaller reservation 2B subsequently arrived from (d). This steady state is perturbed roughly every Kb*R seconds, when the blockade state times out. The next refresh then sends 4B to previous hop (a); presumably this will fail, sending a *ResvErr* message that will re-establish the blockade state, returning to the situation shown in the figure. At the same time, the *ResvErr* message will be forwarded to next hop (c) and to all receivers downstream responsible for the 4B reservations.

3.5 Local Repair

When a route changes, the next *Path* or *Resv* refresh message will establish path or reservation state (respectively) along the new route. To provide fast adaptation to routing changes without the overhead of short refresh periods, the local routing protocol module can notify the RSVP daemon of route changes for particular destinations. The RSVP daemon should use this information to trigger a quick refresh of state for these destinations, using the new route.

The specific rules are as follows:

- When routing detects a change of the set of outgoing interfaces for destination G, RSVP should wait for a short period W, and then send *Path* refreshes for all sessions G/* (i.e., for any session with destination G, regardless of destination port).



Figure 12: Blockading with Shared Style

The short wait period before sending *Path* refreshes is to allow the routing protocol getting settled with the new change(s), and the exact value for W should be chosen accordingly. Currently W = 2 sec is suggested; however, this value should be configurable per interface.

- When a *Path* message arrives with a Previous Hop address that differs from the one stored in the path state, RSVP should send immediate *Resv* refreshes for that session.

3.6 Time Parameters

There are two time parameters relevant to each element of RSVP path or reservation state in a node: the refresh period R between generation of successive refreshes for the state by the neighbor node, and the local state's lifetime L. Each RSVP *Resv* or *Path* message may contain a TIME_VALUES object specifying the R value that was used to generate this (refresh) message. This R value is then used to determine the value for L when the state is received and stored. The values for R and L may vary from hop to hop.

In more detail:

1. Floyd and Jacobson [FJ94] have shown that periodic messages generated by independent network nodes can become synchronized. This can lead to disruption in network services as the periodic messages contend with other network traffic for link and forwarding resources. Since RSVP sends periodic refresh messages, it must avoid message synchronization and ensure that any synchronization that may occur is not stable.

For this reason, the refresh timer should be randomly set to a value in the range [0.5R, 1.5R].

2. To avoid premature loss of state, L must satisfy L >= (K + 0.5)*1.5*R, where K is a small integer. Then in the worst case, K-1 successive messages may be lost without state being deleted. To compute a lifetime L for a collection of state with different R values R0, R1, ..., replace R by max(Ri).

   Currently K = 3 is suggested as the default. However, it may be necessary to set a larger K value for hops with high loss rate. K may be set either by manual configuration per interface, or by some adaptive technique that has not yet been specified.

3. Each *Path* or *Resv* message carries a TIME_VALUES object containing the refresh time R used to generate refreshes. The recipient node uses this R to determine the lifetime L of the stored state created or refreshed by the message.

4. The refresh time R is chosen locally by each node. If the node does not implement local repair of reservations disrupted by route changes, a smaller R speeds up adaptation to routing changes, while increasing the RSVP overhead. With local repair, a router can be more relaxed about R since the periodic refresh becomes only a backstop robustness mechanism. A node may therefore adjust the effective R dynamically to control the amount of overhead due to refresh messages.

   The current suggested default for R is 30 seconds. However, the default should be configurable per interface.

5. When R is changed dynamically, there is a limit on how fast it may increase. Specifically, the ratio of two successive values R2/R1 must not exceed 1 + Slew.Max.

   Currently, Slew.Max is 0.30. With K = 3, one packet may be lost without state timeout while R is increasing 30 percent per refresh cycle.

6. To improve robustness, a node may temporarily send refreshes more often than R after a state change (including initial state establishment).

7. The values of Rdef, K, and Slew.Max used in an implementation should be easily modifiable per interface, as experience may lead to different values. The possibility of dynamically adapting K and/or Slew.Max in response to measured loss rates is for future study.

The granularity of state for refresh and timeout is as follows:

- For reservation state, each FLOWSPEC is independently refreshed and timed out.
- For path state, each sender is independently refreshed and timed out.

3.7 Traffic Policing and Non-Integrated Service Hops

Some QoS services may require traffic policing at some or all of (1) the edge of the network, (2) a merging point for data from multiple senders, and/or (3) a branch point where traffic flow from upstream may be greater than the downstream reservation being requested. RSVP knows where such points occur and must so indicate to the traffic control mechanism. On the other hand, RSVP does not interpret the service embodied in the flowspec and therefore does not know whether policing will actually be applied in any particular case.

The RSVP daemon passes to traffic control a separate policing flag for each of these three situations.

- E_Police_Flag – Entry Policing

  This flag is set in the first-hop RSVP node that implements traffic control (and is therefore capable of policing).

  For example, sender hosts must implement RSVP but currently many of them do not implement traffic control. In this case, the E_Police_Flag should be off in the sender host, and it should only be set on when the first node capable of traffic control is reached. This is controlled by the E_Police flag in SESSION objects.

- M_Police_Flag – Merge Policing

  This flag should be set on for a reservation using a shared style (WF or SE) when flows from more than one sender are being merged.

- B_Police_Flag – Branch Policing

  This flag should be set on when the flowspec being installed is smaller than, or incomparable to, a FLOWSPEC in place on any other interface, for the same FILTER_SPEC and SESSION.

RSVP must also detect and report to receivers the presence of non-RSVP (which implies non-integrated-service compliant) hops in the path. For this purpose, an RSVP daemon sets the Non_RSVP flag bit in SESSION object of *Path* messages. With normal IP forwarding, RSVP can detect a non-RSVP hop by comparing the IP TTL with which a *Path* message is sent to the TTL with which it is received, and set the Non_RSVP bit on. For this purpose, the transmission TTL is placed in the common header.

However, the TTL is not always a reliable indicator of non-RSVP hops, and other means must be used. For example, if the routing protocol uses IP encapsulating tunnels, then the routing protocol must inform RSVP when non-RSVP hops are included. If no automatic mechanism will work, manual configuration will be required. Finally, there may still be cases where an RSVP cannot reliably determine whether or not a non-RSVP hop was used. To report this to the receiver, the SESSION object carries another flag bit, Maybe_RSVP.

3.8 Multihomed Hosts

Accommodating multihomed hosts requires some special rules in RSVP. We use the term 'multihomed host' to cover both hosts (end systems) with more than one network interface and routers that are supporting local application programs.

An application executing on a multihomed host may explicitly specify which interface any given flow will use for sending and/or for receiving data packets, to override the system-specified default interface. The RSVP daemon must be aware of the default, and if an application sets a specific interface, it must also pass that information to RSVP.

- Sending Data

  A sender application uses an API call (SENDER in Section 3.10.1) to declare to RSVP the characteristics of the data flow it will originate. This call may optionally include the local IP address of the sender. If it is set by the application, this parameter must be the interface address for sending the data packets; otherwise, the system default interface is implied.

  The RSVP daemon on the host then sends *Path* messages for this application out the specified interface (only).

- Making Reservations

  A receiver application uses an API call (RESERVE in Section 3.10.1) to request a reservation from RSVP. This call may optionally include the local IP address of the receiver, i.e., the interface address for receiving data packets. In the case of multicast sessions, this is the interface on which the group has been joined. If the parameter is omitted, the system default interface is used.

  In general, the RSVP daemon should send *Resv* messages for an application out the specified interface. However, when the application is executing on a router and the session is multicast, a more complex situation arises. Suppose in this case that a receiver application joins the group on an interface Iapp that differs from Isp, the shortest-path interface to the sender. Then there are two possible ways for multicast routing to deliver data packets to the application. The RSVP daemon must determine which case holds by examining the path state, to decide which incoming interface to use for sending *Resv* messages.

  1. The multicast routing protocol may create a separate branch of the multicast distribution 'tree' to deliver to Iapp. In this case, there will be path state for both Isp and Iapp. The path state on Iapp should only match a reservation from the local application; it must be marked "Local_only" by the RSVP daemon. If "Local_only" path state for Iapp exists, the *Resv* message should be sent out Iapp.

     Note that it is possible for the path state blocks for Isp and Iapp to have the same next hop, if there is an intervening non-RSVP cloud.

2. The multicast routing protocol may forward data within the router from Isp to Iapp. In this case, Iapp will appear in the list of outgoing interfaces of the path state for Isp, and the *Resv* message should be sent out Isp.

3.9 Future Compatibility

We may expect that in the future new object C-Types will be defined for existing object classes, and perhaps new object classes will be defined. It will be desirable to employ such new objects within the Internet using older implementations that do not recognize them. Unfortunately, this is only possible to a limited degree with reasonable complexity. The rules are as follows ('b' represents a bit).

1. Unknown Class

   There are three possible ways that an RSVP implementation can treat an object with unknown class. This choice is determined by the two high-order bits of the Class-Num octet, as follows.

   - Class-Num = 0bbbbbbb

     The entire message should be rejected and an "Unknown Object Class" error returned.
   - Class-Num = 10bbbbbb

     The node should ignore the object, neither forwarding it nor sending an error message.
   - Class-Num = 11bbbbbb

     The node should ignore the object but forward it, unexamined and unmodified, in all messages resulting from the state contained in this message.

   For example, suppose that a *Resv* message that is received contains an object of unknown class number 11bbbbbb. Such an object should be saved in the reservation state without further examination; however, only the latest object with a given (unknown class, C-Type) pair should be saved. When a *Resv* message is forwarded, it should include copies of such saved unknown-class objects from all reservations that are merged to form the new *Resv* message.

   Note that objects with unknown class cannot be merged; however, unmerged objects may be forwarded until they reach a node that knows how to merge them. Forwarding objects with unknown class enables incremental deployment of new objects; however, the scaling limitations of doing so must be carefully examined before a new object class is deployed with both high bits on.

   These rules should be considered when any new Class-Num is defined.

2. Unknown C-Type for Known Class

   One might expect the known Class-Num to provide information that could allow intelligent handling of such an object. However, in practice such class-dependent handling is complex, and in many cases it is not useful.

   Generally, the appearance of an object with unknown C-Type should result in rejection of the entire message and generation of an error message (*ResvErr* or *PathErr* as appropriate). The error message will include the Class-Num and C-Type that failed (see Appendix B); the end system that originated the failed message may be able to use this information to retry the request using a different C-Type object, repeating this process until it runs out of alternatives or succeeds.

   Objects of certain classes (FLOWSPEC, ADSPEC, and POLICY_DATA) are opaque to RSVP, which simply hands them to traffic control or policy modules. Depending upon its internal rules, either of the latter modules may reject a C-Type and inform the RSVP daemon; RSVP should then reject the message and send an error, as described in the previous paragraph.

3.10 RSVP Interfaces

RSVP on a router has interfaces to routing and to traffic control. RSVP on a host has an interface to applications (i.e, an API) and also an interface to traffic control (if it exists on the host).

3.10.1 Application/RSVP Interface

This section describes a generic interface between an application and an RSVP control process. The details of a real interface may be operating-system dependent; the following can only suggest the basic functions to be performed. Some of these calls cause information to be returned asynchronously.

- Register Session

```
Call: SESSION( DestAddress , ProtocolId, DstPort ,

            [ , SESSION_object ]

            [ , Upcall_Proc_addr ] )  -> Session-id
```

  This call initiates RSVP processing for a session, defined by DestAddress together with ProtocolId and possibly a port number DstPort. If successful, the SESSION call returns immediately with a local session identifier Session-id, which may be used in subsequent calls.

  The Upcall_Proc_addr parameter defines the address of an upcall procedure to receive asynchronous error or event notification; see below. The SESSION_object parameter is included as an escape mechanism to support some more general definition of the session ("generalized destination port"), should that be necessary in the future. Normally SESSION_object will be omitted.

- Define Sender

```
Call: SENDER( Session-id,

            [ , Source_Address ]  [ , Source_Port ]

            [ , Sender_Template ]

            [ , Sender_Tspec ]   [ , Data_TTL ]
```

```
[ , Sender_Policy_Data ] )
```

A sender uses this call to define, or to modify the definition of, the attributes of the data stream. The first SENDER call for the session registered as 'Session-id' will cause RSVP to begin sending *Path* messages for this session; later calls will modify the path information.

The SENDER parameters are interpreted as follows:

- Source_Address

  This is the address of the interface from which the data will be sent. If it is omitted, a default interface will be used. This parameter is needed on a multihomed sender host.
- Source_Port

  This is the UDP/TCP port from which the data will be sent. If it is omitted or zero, the port is "wild" and can match any port in a FILTER_SPEC.
- Sender_Template

  This parameter is included as an escape mechanism to support a more general definition of the sender (*generalized source port*). Normally this parameter may be omitted.
- Sender_Tspec

  This optional parameter describes the traffic flow to be sent. It may be included to prevent over-reservation on the initial hops.
- Data_TTL

  This is the (non-default) IP Time-To-Live parameter that is being supplied on the data packets. It is needed to ensure that Path messages do not have a scope larger than multicast data packets.
- Sender_Policy_Data

  This optional parameter passes policy data for the sender. This data may be supplied by a system service, with the application treating it as opaque.

- Reserve

```
Call: RESERVE( session-id, [ receiver_address , ]

            [ CONF_flag, ] style, style-dependent-parms )
```

A receiver uses this call to make or to modify a resource reservation for the session registered as 'session-id'. The first RESERVE call will initiate the periodic transmission of *Resv* messages. A later RESERVE call may be given to modify the parameters of the earlier call (but note that changing existing reservations may result in admission control failures).

The optional 'receiver_address' parameter may be used by a receiver on a multihomed host (or router); it is the IP address of one of the node's interfaces. The CONF_flag should be

set on if a reservation confirmation is desired, off otherwise. The 'style' parameter indicates the reservation style. The rest of the parameters depend upon the style; generally these will include appropriate flowspecs, filter specs, and possibly receiver policy data objects.

The RESERVE call returns immediately. Following a RESERVE call, an asynchronous ERROR/EVENT upcall may occur at any time.

- Release

```
Call: RELEASE( session-id )
```

This call removes RSVP state for the session specified by session-id. The node then sends appropriate teardown messages and ceases sending refreshes for this session-id.

- Error/Event Upcalls

The general form of a upcall is as follows:

```
Upcall: <Upcall_Proc>( ) -> session-id, Info_type,

                information_parameters
```

Here *Upcall_Proc* represents the upcall procedure whose address was supplied in the SESSION call. This upcall may occur asynchronously at any time after a SESSION call and before a RELEASE call, to indicate an error or an event.

Currently there are five upcall types, distinguished by the Info_type parameter. The selection of information parameters depends upon the type.

1. Info_type = PATH_EVENT

   A Path Event upcall results from receipt of the first *Path* message for this session, indicating to a receiver application that there is at least one active sender.

```
Upcall: <Upcall_Proc>( ) -> session-id,

                Info_type=PATH_EVENT,

                flags,

                Sender_Tspec, Sender_Template,

                [ , Advert ] [ , Policy_data ]
```

   This upcall presents the Sender_Tspec and the Sender_Template from a *Path* message; it also passes the advertisement and policy data if they are present. The possible flags correspond to Non_RSVP and Maybe_RSVP flags of the SESSION object.

2. Info_type = RESV_EVENT
   A Resv Event upcall is triggered by the receipt of the first *Resv* message, or by modification of a previous reservation state, for this session.

```
Upcall: <Upcall_Proc>( ) -> session-id,

            Info_type=RESV_EVENT,

            Style, Flowspec, Filter_Spec_list,

            [ , Policy_data ]
```

   Here 'Flowspec' will be the effective QoS that has been received. Note that an FF-style *Resv* message may result in multiple RESV_EVENT upcalls, one for each flow descriptor.
3. Info_type = PATH_ERROR
   An Path Error event indicates an error in sender information that was specified in a SENDER call.

```
Upcall: <Upcall_Proc>( ) -> session-id,

              Info_type=PATH_ERROR,

              Error_code , Error_value ,

              Error_Node , Sender_Template,

              [ Policy_data_list ]
```

   The Error_code parameter will define the error, and Error_value may supply some additional (perhaps system-specific) data about the error. The Error_Node parameter will specify the IP address of the node that detected the error. The Policy_data_list parameter, if present, will contain any POLICY_DATA objects from the failed *Path* message.
4. Info_type = RESV_ERR
   An Resv Error event indicates an error in a reservation message to which this application contributed.

```
Upcall: <Upcall_Proc>( ) -> session-id,

              Info_type=RESV_ERROR,

              Error_code , Error_value ,
```

```
                    Error_Node , Error_flags ,

                    Flowspec, Filter_spec_list,

                    [ Policy_data_list ]
```

The Error_code parameter will define the error and Error_value may supply some additional (perhaps system-specific) data. The Error_Node parameter will specify the IP address of the node that detected the event being reported.

There are two Error_flags:

- InPlace
  This flag may be on for an Admission Control failure, to indicate that there was, and is, a reservation in place at the failure node. This flag is set at the failure point and forwarded in *ResvErr* messages.
- NotGuilty
  This flag may be on for an Admission Control failure, to indicate that the flowspec requested by this receiver was strictly less than the flowspec that got the error. This flag is set at the receiver API.

Filter_spec_list and Flowspec will contain the corresponding objects from the **error flow descriptor** (see Section 3.1.6). List_count will specify the number of FILTER_SPECS in Filter_spec_list. The Policy_data _list parameter will contain any POLICY_DATA objects from the *ResvErr* message.

5. Info_type = RESV_CONFIRM

   A Confirmation event indicates that a *ResvConf* message was received.

```
   Upcall: <Upcall_Proc>( ) -> session-id,

                    Info_type=RESV_CONFIRM,

                    Style, List_count,

                    Flowspec, Filter_spec_list,

                    [ Policy_data ]
```

   The parameters are interpreted as in the Resv Error upcall.

Although RSVP messages indicating path or resv events may be received periodically, the API should make the corresponding asynchronous upcall to the application only on the first occurrence or when the information to be reported changes. All error and confirmation events should be reported to the application.

3.10.2 RSVP/Traffic Control Interface

In an RSVP-capable node, enhanced QoS is achieved by a group of inter-related traffic control functions: a packet classifier, an admission control module, and a packet scheduler. This section describes a generic RSVP interface to traffic control.

- Make a Reservation

  ```
  Call: Rhandle =  TC_AddFlowspec( Interface, TC_Flowspec,

                                   TC_Tspec, Police_Flags )
  ```

  The TC_Flowspec parameter defines the desired effective QoS to admission control; its value is computed as the maximum over the flowspecs of different next hops (see the Compare_Flowspecs call below). It contains the effective reservation Tspec Resv_Te (although the RSVP daemon itself has no means to extract the Tspec). The TC_Tspec parameter defines the effective sender Tspec Path_Te (see Section 2.3). We assume that traffic control takes the GLB of Resv_Te and Path_Te (see step (4) in Section 2.3). The Police_Flags parameter carries the three flags E_Police_Flag, M_Police_Flag, and B_Police_Flag; see Section 3.7.

  The TC_AddFlowspec call returns an error code if Flowspec is malformed or if the requested resources are unavailable. Otherwise, it establishes a new reservation channel corresponding to Rhandle. It returns the opaque number Rhandle for subsequent references to this reservation.

- Modify Reservation

  ```
  Call: TC_ModFlowspec( Interface, Rhandle, new_Flowspec,

                                   Sender_Tspec,  Police_flags )
  ```

  This call is used to modify an existing reservation. New_Flowspec is passed to Admission Control; if it is rejected, the current flowspec is left in force. The corresponding filter specs, if any, are not affected. The other parameters are defined as in TC_AddFlowspec.

- Delete Flowspec

  ```
  Call: TC_DelFlowspec( Interface, Rhandle )
  ```

  This call will delete an existing reservation, including the flowspec and all associated filter specs.

- Add Filter Spec

```
Call: FHandle = TC_AddFilter( Interface, Rhandle,

                              Session , FilterSpec )
```

This call is used to associate an additional filter spec with the reservation specified by the given Rhandle, following a successful TC_AddFlowspec call. This call returns a filter handle FHandle.

- Delete Filter Spec

  ```
  Call: TC_DelFilter( Interface, FHandle )
  ```

  This call is used to remove a specific filter, specified by FHandle.

- OPWA Update

  ```
  Call: TC_Advertise( Interface, Adspec )

                                        -> New_Adspec
  ```

  This call is used for OPWA to compute the outgoing advertisement New_Adspec for a specified interface.

- Preemption Upcall

  ```
  Upcall: TC_Preempt() -> RHandle, Reason_code
  ```

  In order to grant a new reservation request, the admission control and/or policy modules may preempt an existing reservation. This might be reflected in an upcall to RSVP, passing the RHandle of the preempted reservation and a sub-code indicating the reason.

3.10.3 RSVP/Routing Interface

An RSVP implementation needs the following support from the packet forwarding and routing mechanisms of the node.

- Promiscuous Receive Mode for RSVP Messages

  Packets received for IP protocol 46 but not addressed to the node must be diverted to the RSVP program for processing, without being forwarded. On a router, the identity of the interface, real or virtual, on which it is received as well as the IP source address and IP TTL with which it arrived must also be available to the RSVP daemon.

The RSVP messages to be diverted will carry the Router Alert IP option, which can be used to pick them out of a high-speed forwarding path. Alternatively, the node can intercept all protocol 46 packets.

When an RSVP message (fragment) is handed to RSVP, the actual length received must also be passed.

- Route Query

  To forward *Path* and *PathTear* messages, an RSVP daemon must be able to query the routing daemon(s) for routes.

```
Ucast_Route_Query( [ SrcAddress, ] DestAddress,

                   Notify_flag ) -> OutInterface

Mcast_Route_Query( [ SrcAddress, ] DestAddress,

                   Notify_flag )

                -> [ IncInterface, ] OutInterface_list
```

  Depending upon the routing protocol, the query may or may not depend upon SrcAddress, i.e., upon the sender host IP address, which is also the IP source address of the message. Here IncInterface is the interface through which the packet is expected to arrive; some multicast routing protocols may not provide it. If the Notify_flag is True, routing will save state necessary to issue unsolicited route change notification callbacks (see below) whenever the specified route changes.

  A multicast route query may return an empty OutInterface_list if there are no receivers downstream of a particular router. A route query may also return a 'No such route' error, probably as a result of a transient inconsistency in the routing (since a *Path* or *PathTear* message for the requested route did arrive at this node). In either case, the local state should be updated as requested by the message, which cannot be forwarded further. Updating local state will make path state available immediately for a new local receiver, or it will tear down path state immediately.

- Route Change Notification

  If requested by a route query with the Notify_flag True, the routing daemon may provide an asynchronous callback to the RSVP daemon that a specified route has changed.

```
Ucast_Route_Change( ) -> [ SrcAddress, ] DestAddress,

                                   OutInterface
```

```
Mcast_Route_Change( ) -> [ SrcAddress, ] DestAddress,

                [ IncInterface, ] OutInterface_list
```

- Outgoing Link Specification

  RSVP must be able to force a (multicast) datagram to be sent on a specific outgoing virtual link, bypassing the normal routing mechanism. A virtual link may be a real outgoing link or a multicast tunnel. Outgoing link specification is necessary to send different versions of an outgoing *Path* message on different interfaces. It is also necessary in some cases to avoid routing loops.

- Source Address Specification

  RSVP must be able to specify the IP source address to be used when sending *Path* messages.

- Interface List Discovery

  RSVP must be able to learn what real and virtual interfaces are active, with their IP addresses.

  It should be possible to logically disable an interface for RSVP. When an interface is disabled for RSVP, a *Path* message should never be forwarded out that interface, and if an RSVP message is received on that interface, the message should be silently discarded (perhaps with local logging).

3.10.4 Service-Dependent Manipulations

Flowspecs, Tspecs, and Adspecs are opaque objects to RSVP; their contents are defined in service specification documents. In order to manipulate these objects, RSVP daemon must have available to it the following service-dependent routines.

- Compare Flowspecs

```
Compare_Flowspecs( Flowspec_1, Flowspec_2 ) ->

                                        result_code
```

  The possible result_codes indicate: flowspecs are equal, Flowspec_1 is greater, Flowspec_2 is greater, flowspecs are incomparable but LUB can be computed, or flowspecs are incompatible.

  Note that comparing two flowspecs implicitly compares the Tspecs that are contained. Although the RSVP daemon cannot itself parse a flowspec to extract the Tspec, it can use the Compare_Flowspecs call to implicitly calculate Resv_Te (see Section 2.3).

- Compute LUB of Flowspecs

```
LUB_of_Flowspecs( Flowspec_1, Flowspec_2 ) ->

                                        Flowspec_LUB
```

- Compute GLB of Flowspecs

```
GLB_of_Flowspecs( Flowspec_1, Flowspec_2 ) ->

                                        Flowspec_GLB
```

- Compare Tspecs

```
Compare_Tspecs( Tspec_1, Tspec_2 ) -> result_code
```

  The possible result_codes indicate: Tspecs are equal, or Tspecs are unequal.

- Sum Tspecs

```
Sum_Tspecs( Tspec_1, Tspec_2 ) -> Tspec_sum
```

  This call is used to compute Path_Te (see Section 2.3).

4 Message Processing Rules

This section provides a generic description of the rules for RSVP operation. It is intended to outline a set of algorithms that will accomplish the needed function, omitting some details.

This section assumes the generic interface calls defined in Section 3.10 and the following data structures. An actual implementation may use additional or different data structures and interfaces. The data structure fields that a shown are required unless they are explicitly labelled as optional.

- PSB – Path State Block

  Each PSB holds path state for a particular (session, sender) pair, defined by SESSION and SENDER_TEMPLATE objects, respectively, received in a *Path* message.

  PSB contents include the following values from a *Path* message:

  - Session
  - Sender_Template
  - Sender_Tspec
  - The previous hop IP address and the Logical Interface Handle (LIH) from a PHOP object
  - The remaining IP TTL
  - POLICY_DATA and/or ADSPEC objects (optional)
  - Non_RSVP and Maybe_RSVP flags; see Section 3.7.
  - E_Police flag (Section 3.7)
  - Local_Only flag (Section 3.8)

  In addition, the PSB contains the following information provided by routing: OutInterface_list, which is the list of outgoing interfaces for this (sender, destination), and IncInterface, which is the expected incoming interface. For a unicast destination, OutInterface_list contains one entry and IncInterface is undefined.

- RSB – Reservation State Block

  Each RSB holds a reservation request that arrived in a particular *Resv* message, corresponding to the triple: (session, next hop, Filter_spec_list). Here "Filter_spec_list" may be a list of FILTER_SPECs (for SE style), a single FILTER_SPEC (FF style), or empty (WF style). We define a virtual object type "FILTER_SPEC*" for such a data structure.

  RSB contents include:

  - Session specification

- Next hop IP address
- Filter_spec_list
- The outgoing (logical) interface OI on which the reservation is to be made or has been made (required).
- Style
- Flowspec
- A POLICY_DATA object (optional)
- A SCOPE object (optional, depending on style)
- A RESV_CONFIRM object (optional)

- TCSB – Traffic Control State Block

  Each TCSB holds the reservation specification that has been handed to traffic control for a specific outgoing interface. In general, TCSB information is derived from RSB's for the same outgoing interface. Each TCSB defines a single reservation for a particular triple: (session, OI, Filter_spec_list). TCSB contents include:

  - Session
  - OI
  - Filter_spec_list
  - TC_Flowspec, the effective flowspec, i.e., the maximum over the corresponding FLOWSPEC values from matching RSB's. TC_Flowspec is passed to traffic control to make the actual reservation. The Tspec part of TC_Flowspec is the effective reservation Tspec Resv_Te (Section 2.3).
  - TC_Tspec, equal to Path_Te, the effective sender Tspec.
  - Police Flags

    The flags E_Police_Flag, M_Police_Flag, and B_Police_Flag are defined in Section 3.7.
  - Rhandle, F_Handle_list

    Handles returned by the traffic control interface, corresponding to the reservation (flowspec) and to the list of filter specs.

- BSB – Blockade State Block

  Each BSB contains an element of blockade state. Depending upon the reservation style in use, the BSB's may be per (session, sender_template) or per (session, PHOP). In practice, an implementation might embed a BSB within a PSB; however, for clarity we describe BSB's independently.

  The contents of a BSB include:

  - Session
  - Sender_Template (which is also a filter spec)

- PHOP
- FLOWSPEC Qb
- Blockade timer Tb

The following other variables are also used in this section: Boolean flags Path_Refresh_Needed, Resv_Refresh_Needed, Tear_Needed, Need_Scope, B_Merge, and NeworMod, and Refresh_PHOP_list, a variable-length list of PHOPs to be refreshed.

MESSAGE ARRIVES

Verify version number and RSVP checksum, and discard message if any mismatch is found.

If the message type is not *Path* or *PathTear* and if the IP destination address does not match any of the addresses of the local interfaces, then forward the message to IP destination address and return.

Verify the INTEGRITY object, if any. If the check fails, discard the message and return.

Reassemble fragments of message.

Parse the sequence of objects in the message, and discard message if any required objects are missing. Verify the length field of the common header, and discard message if there is a mismatch.

Verify the consistent use of port fields. If the DstPort in the SESSION object is zero but the SrcPort in a SENDER_TEMPLATE or FILTER_SPEC object is non-zero, the the message has a "conflicting source port" error; discard the message and return.

Further processing depends upon message type.

Path MESSAGE ARRIVES

Process the **sender descriptor** object sequence in the message as follows. The Path_Refresh_Needed and Resv_Refresh_Needed flags are initially off.

- If there is a POLICY_DATA object, verify it; if it is unacceptable, build and send a "Administrative Rejection" *PathErr* message, drop the *Path* message, and return.
- Search for a path state block (PSB) whose (session, sender_template) pair matches the corresponding objects in the message.
- If, during the PSB search, a PSB is found whose session matches the DestAddress and Protocol Id fields of the received SESSION object, but the DstPorts differ and one is zero, then build and send a "Conflicting Dst Port" *PathErr* message, drop the *Path* message, and return.

- If, during the PSB search, a PSB is found with a matching sender host but the SrcPorts differ and one of the SrcPorts is zero, then build and send an "Ambiguous Path" *PathErr* message, drop the *Path* message, and return.
- If there was no matching PSB, then:
  1. Create a new PSB.
  2. Copy contents of the SESSION, SENDER_TEMPLATE, SENDER_TSPEC, and PHOP (IP address and LIH) objects into the PSB.
  3. Calculate initial routing information. If the sender is from the local API, OutInterface_List is set to the single interface whose address matches the sender address, and IncInterface is undefined. Otherwise, call the appropriate Route_Query routine, using DestAddress from SESSION and (for multicast routing) SrcAddress from SENDER_TEMPLATE. Store the values of OutInterface_list and IncInterface into the PSB.
  4. If IncInterface is defined and if a multicast message arrived on an interface different from IncInterface, turn on the Local_Only flag in the PSB.
  5. If this is the first PSB for the session, set a refresh timer for the session.
  6. Turn on the Path_Refresh_Needed flag.
- Otherwise (there is a matching PSB and there is no dest port conflict):
  1. If there is no route change notification in place, call the appropriate Route_Query routine using DestAddress from SESSION and (for multicast routing) SrcAddress from Sender_Template.
     - If the OutInterface_list that is returned differs from that in the PSB, then execute the PATH LOCAL REPAIR event sequence below.
     - If a multicast message arrived on an interface different from IncInterface, then execute the RESV REFRESH event sequence below for the previous hop.
  2. If the PHOP IP address, the LIH, or Sender_Tspec differs between the message and the PSB, copy the new value into the PSB and turn on the Path_Refresh_Needed flag.
- If the message contains an ADSPEC object, copy it into the PSB.
- Start or Restart the cleanup timer for the PSB.
- Copy E_Police flag from SESSION object into PSB.
- Store the received TTL into the PSB.

  If the the received TTL differs from Send_TTL in the RSVP common header, set the Non_RSVP flag on in the PSB.
- The Path_Refresh_Needed flag is now set if the path state is new or modified. If so:
  1. If this *Path* message came from a network interface and not from a local application, make a Path Event upcall for each local application for this session:

     ```
     Call: <Upcall_Proc>( session-id, PATH_EVENT,
     ```

```
                    flags, sender_tspec, sender_template,
                    [ADSPEC], [POLICY_DATA] )
```

2. Execute the PATH REFRESH event sequence (below) for the sender defined by the PSB.
3. If there is no reservation state for this SESSION (i.e., no RSB's exist), then drop the *Path* message and return.
4. Otherwise (there is reservation state):
   - Execute the event sequence UPDATE TRAFFIC CONTROL below, to update the local traffic control state if necessary. This will turn on the Resv_Refresh_Needed flag if the traffic control state changes; if so, execute the RESV REFRESH event sequence (below) for the sender in the PSB.
     However, if the *Path* message came from a local application, then make a RESV_EVENT upcall to that application.

- Drop the *Path* message and return.

PathTear MESSAGE ARRIVES

- Search for a PSB whose (Session, Sender_Template) pair matches the corresponding objects in the message. If no matching PSB is found, drop the *PathTear* message and return.
- Forward a copy of the *PathTear* message to each outgoing interface listed in OutInterface_list of the PSB.
- Find each RSB that matches this PSB, i.e., that whose Filter_spec_list matches Sender_Template in the PSB and whose OI is included in OutInterface_list.

  If this RSB matches no other PSB, then tear down the RSB, as described below under *ResvTear* MESSAGE ARRIVES.
- Delete the PSB.
- Drop the *PathTear* message and return.

PathErr MESSAGE ARRIVES

- Search for a PSB whose (SESSION, SENDER_TEMPLATE) pair matches the corresponding objects in the message. If no matching PSB is found, drop the *PathErr* message and return.
- If the previous hop address in the PSB is the local API, make an error upcall to the application:

```
Call: <Upcall_Proc>( session-id, PATH_ERROR,
                     Error_code, Error_value,
                     Node_Addr, Sender_Template,
```

```
[Policy_Data] )
```

Any SENDER_TSPEC or ADSPEC object in the message is ignored.
Otherwise, send a copy of the *PathErr* message to the PHOP IP address.

- Drop the *PathErr* message and return.

Resv MESSAGE ARRIVES

Initially, Refresh_PHOP_list is empty and the Resv_Refresh_Needed and NeworMod flags are off. These variables are used to control immediate reservation refreshes.

- Determine the Outgoing Interface OI
  The logical outgoing interface OI is taken from the LIH in the NHOP object. (If the physical interface is not implied by the LIH, it can be learned from the interface matching the IP destination address).
- Check the SESSION object.
  If there are no existing PSB's for SESSION then build and send a *ResvErr* message (as described later) specifying "No path information", drop the *Resv* message, and return.
- Check the S_POLICY_DATA object.
  If there is an S_POLICY_DATA object in the message, check permission to create a reservation for the session. If the check fails, build and send an "Administrative rejection" *ResvErr* message, drop the *Resv* message, and return. Otherwise, copy the S_POLICY_DATA object into the RSB.
- Check for incompatible styles.
  If any existing RSB for the session has a style that is incompatible with the style of the message, build and send a *ResvErr* message specifying "Conflicting Style", drop the *Resv* message, and return.

Process the **flow descriptor list** to make reservations, as follows, depending upon the style. The following uses a filter spec list struct Filtss, of type FILTER_SPEC* (defined earlier).

For FF style: execute the following steps independently for each **flow descriptor** in the message, i.e., for each (FLOWSPEC, Filtss) pair. Here the structure Filtss consists of the FILTER_SPEC from the flow descriptor.

For SE style, execute the following steps once for (FLOWSPEC, Filtss), with Filtss consisting of the list of FILTER_SPEC objects from the flow descriptor.

For WF style, execute the following steps once for (FLOWSPEC, Filtss), with Filtss an empty list.

- If the DstPort in the SESSION object is zero but the SrcPort in a FILTER_SPEC object (in Filtss) is non-zero, build nd send a "Conflicting Src Port" *ResvErr* message, drop the *Resv* message, and return.

- Check the path state, as follows.
  1. Locate the set of PSBs (senders) whose SENDER_TEMPLATEs match Filtss and whose OutInterface_list includes OI.
     If this set is empty, build and send an error message specifying "No sender information", and continue with the next flow descriptor in the *Resv* message.
  2. If the style has explicit sender selection (e.g., FF or SE) and if any FILTER_SPEC included in Filtss matches more than one PSB, build and send a *ResvErr* message specifying "Ambiguous filter spec" and continue with the next flow descriptor in the *Resv* message.
  3. Add the PHOP from the PSB to Refresh_PHOP_list, if the PHOP is not already on the list.
- Find or create a reservation state block (RSB) for the triple: (session, NHOP, Filtss). Call this the *active RSB*.
- If the active RSB is new:
  1. Set the session, NHOP, OI and style of the RSB from the message.
  2. Copy Filtss into the Filter_spec_list of the RSB.
  3. Copy the FLOWSPEC and any SCOPE object from the message into the RSB.
  4. Set NeworMod flag on.
- Start or restart the cleanup timer on the the active RSB.
- If there is a RESV_CONFIRM in the message, turn on Resv_Refresh_Needed and save the object in the RSB.
- If the active RSB is not new, check whether STYLE, FLOWSPEC or SCOPE objects have changed; if so, copy changed object into RSB and turn on the NeworMod flag.
- If NeworMod flag is off, continue with the next **flow descriptor** in the *Resv* message, if any.
- Otherwise (the NeworMod flag is on, i.e., the active RSB is new or modified), execute the UPDATE TRAFFIC CONTROL event sequence (below). If the result is to modify the traffic control state, it will turn on the Resv_Refresh_Needed flag.
- For any local sender, make an RESV_EVENT upcall to the application:

```
Call: <Upcall_Proc>( session-id, RESV_EVENT,
           style, Flowspec, Filter_spec_list,
           [POLICY_DATA] )
```

  where the parameters come from the active RSB.
- Continue with the next flow descriptor.
- When all flow descriptors have been processed, check the Resv_Refresh_Needed flag. If it is now on, execute the RESV REFRESH sequence (below) for each PHOP in Refresh_PHOP_list.

- Drop the *Resv* message and return.

If processing a *Resv* message finds an error, a *ResvErr* message is created containing flow descriptor and an ERRORS object. The Error Node field of the ERRORS object is set to the IP address of OI, and the message is sent unicast to NHOP.

ResvTear MESSAGE ARRIVES

A *ResvTear* message arrives with an IP destination address matching outgoing interface OI. Flags Tear_Needed and Resv_Refresh_Needed are initially off and Refresh_PHOP_list is empty.

- Process the STYLE object and the **flow descriptor list** in the *ResvTear* message to tear down local reservation state, as follows. We assume a filter spec list struct Filtss, of type FILTER_SPEC* (defined earlier).

  For FF style: execute the following steps independently for each **flow descriptor** in the message, i.e., for each (FLOWSPEC, Filtss) pair. Here the structure Filtss consists of the FILTER_SPEC from the flow descriptor.

  For SE style, execute the following steps once for (FLOWSPEC, Filtss), with Filtss consisting of the list of FILTER_SPEC objects from the flow descriptor.

  For WF style, execute the following steps once for (FLOWSPEC, Filtss), with Filtss an empty list.

  1. Find matching RSB for the triple: (SESSION, NHOP, Filtss); call this the active RSB. If no active RSB is found, continue with next flow descriptor.
  2. Delete the active RSB.
  3. Execute the event sequence UPDATE TRAFFIC CONTROL (below) to update the traffic control state to be consistent with the reservation state.
  4. Search for a TCSB remaining for the (session, OI, Filtss) triple; if not, set the Tear_Needed flag on.
  5. Continue with the next flow descriptor.

- If Tear_Needed and Resv_Refresh_Needed flags are both off, then drop the *ResvTear* message and return.
- If Tear_Needed is off but Resv_Refresh_Needed is on, then execute the RESV REFRESH sequence for each PHOP in Refresh_PHOP_list, drop the *ResvTear* message, and return.
- Otherwise (Tear_Needed is on), need to forward *ResvTear* and/or *Resv* refresh messages.

  Do the following for each PSB whose OutInterface_list includes the outgoing interface OI:

  1. Pick each flow descriptor Fj in the *ResvTear* message whose FILTER_SPEC matches the PSB, and do the following.
     - If there is no RSB whose FILTER_SPEC matches the PSB, then add Fj to the new *ResvTear* message being built.

- Otherwise (there is a matching RSB), note the PSB as needing a *Resv* refresh message and set the Resv_Refresh_Needed flag True.

2. If the new *ResvTear* message contains any flow descriptors, send it to PHOP in the PSB.

- If the Resv_Refresh_Needed flag is now on, execute the RESV REFRESH sequence (below) for each PHOP in Refresh_PHOP_list.
- Drop the *ResvTear* message and return.

ResvErr MESSAGE ARRIVES

A *ResvErr* message arrives through the (real) incoming interface In_If.

- If there is no path state for SESSION, drop the *ResvErr* message and return.
- If the Error Code = 01 (Admission Control failure), do special processing as follows:
  1. Find or create a Blockade State Block (BSB), in the following style-dependent manner.
     For WF (wildcard) style, there will be one BSB per (session, PHOP) pair.
     For FF style, there will be one BSB per (session, filter_spec) pair. Note that an FF style *ResvErr* message carries only one flow descriptor.
     For SE style, there will be one BSB per (session, filter_spec), for each filter_spec contained in the filter spec list of the flow descriptor.
  2. For each BSB in the preceding step, set (or replace) its FLOWSPEC Qb with FLOWSPEC from the message, and set (or reset) its timer Tb to Kb*R seconds [Section 3.4]. If the BSB is new, set its PHOP value, and set its Sender_Template equal to the appropriate filter_spec from the message.
  3. Partially execute the RESV REFRESH event sequence shown below, for the previous hop PHOP.
     In particular, execute the refresh sequence with the B_Merge flag off. If this results in no refresh messages being generated, because all matching reservations are blockaded, do not turn B_Merge on but instead exit the refresh sequence and return here.
- For all *ResvErr* messages, execute the following for each RSB for this session whose OI differs from In_If and whose Filter_spec_list has at least one filter spec in common with the FILTER_SPEC* in the *ResvErr* message. For WF style, empty FILTER_SPEC* structures are assumed to match.
  1. If Error_Code = 01 and the InPlace flag is 1 and one or more of the BSB's found/created above has a Qb that is strictly greater than Flowspec in the RSB, then continue with the next matching RSB, if any.
  2. If NHOP in the RSB is the local API, then:
     - If the FLOWSPEC in the *ResvErr* message is strictly greater than the RSB Flowspec, then turn on the NotGuilty flag in the ERROR_SPEC.

– Deliver an error upcall to application:

```
Call: <Upcall_Proc>( session-id, RESV_ERROR,
                Error_code, Error_value,
                     Node_Addr,  Error_flags,
                     Flowspec, Filter_Spec_List,
                     [Policy_data] )
```

and continue with the next RSB.

3. If the style has wildcard sender selection, use the SCOPE object SC.In from the *ResvErr* message to construct a SCOPE object SC.Out to be forwarded. SC.Out should contain those sender addresses that appeared in SC.In and that route to OI [LIH?], as determined by scanning the PSB's. If SC.Out is empty, continue with the next RSB.
4. Create a new *ResvErr* message containing the **error flow descriptor** and send to the NHOP address specified by the RSB. Include SC.Out if the style has wildcard sender selection.
5. Continue with the next RSB.

- Drop the *ResvErr* message and return.

RESV CONFIRM ARRIVES

- If the (unicast) IP address found in the RESV_CONFIRM object in the *ResvConf* message matches an interface of the node, a confirmation upcall is made to the matching application:

```
Call: <Upcall_Proc>( session-id, RESV_CONFIRM,
         Error_code, Error_value, Node_Addr,
              LUB-Used, nlist, Flowspec,
              Filter_Spec_List, NULL, NULL )
```

- Otherwise, the *ResvConf* message is forwarded immediately to the address in the IP address in its RESV_CONFIRM object.
- Drop the *ResvConf* message and return.

UPDATE TRAFFIC CONTROL

The sequence is invoked by the *Path* MESSAGE ARRIVES or the *Resv* MESSAGE ARRIVES sequence, to (re-)calculate and adjust the local traffic control state in accordance with the current reservation and path state. If the result is to modify the traffic control state, this sequence turns on the Resv_Refresh_Needed flag.

- Compute the traffic control parameters using the following steps.
  1. Consider the set of RSB's matching SESSION and OI from the message.
     - Compute the effective kernel flowspec, TC_Flowspec, as the maximum/LUB of the FLOWSPEC values in these RSB's.
     - Compute the effective traffic control filter spec (list) TC_Filter_Spec*, by merging the Filter_spec_lists from these RSB's.
  2. Scan all RSB's matching session and Filtss, for all OI. Set TC_B_Police_flag on if TC_Flowspec is smaller than, or incomparable to, any FLOWSPEC in those RSB's.
  3. Locate the set of PSBs (senders) whose SENDER_TEMPLATEs match Filter_spec_list in the active RSB and whose OutInterface_list includes OI.
  4. Set TC_E_Police_flag on if any of these PSBs have their E_Police flag on. Set TC_M_Police_flag on if it is a shared style and there is more than one PSB in the set.
  5. Compute Path_Te as the sum of the SENDER_TSPEC objects in this set of PSBs.
- Search for a TCSB matching SESSION and OI; for distinct style (FF), it must also match Filter_spec_list.

  If none is found, create a new TCSB.
- If TCSB is new:
  1. Store TC_Flowspec, TC_Filter_Spec*, Path_Te, and the police flags into TCSB.
  2. Turn the Resv_Refresh_Needed flag on and make the traffic control call:

```
Rhandle = TC_AddFlowspec( OI, TC_Flowspec,
                                Path\_Te, police_flags)
```

  3. If this call succeeds, record Rhandle in the TCSB and, for each filter_spec F in TC_Filter_Spec*, call:

```
Fhandle = TC_AddFilter( OI, Rhandle, Session, F)
```

     and record the returned Fhandle in the TCSB.
  4. Otherwise, build and send a *ResvErr* message specifying "Admission control failed" and with the InPlace flag off.
- If TCSB is not new but the TC_Flowspec, Path_Te, and/or police flags just computed differ from corresponding values in the TCSB, then:
  1. Turn the Resv_Refresh_Needed flag on and make the traffic control call:

```
TC_ModFlowspec( OI, Rhandle, TC_Flowspec,
                               Path_Te, police_flags )
```

2. If this call fails, build and send a *ResvErr* message specifying "Admission control failed" and with the InPlace bit on. If the call succeeds, update the TCSB with the new values.

- If the TCSB is not new but the TC_Filter_Spec* just computed differ from the FILTER_SPEC* in the TCSB, then:

  1. Make an appropriate set of TC_DelFilter and TC_AddFilter calls to transform the Filter_spec_list in the TCSB into the new TC_Filter_Spec*.

- Return to the event sequence that invoked this one.

PATH REFRESH

This sequence sends a path refresh for a particular sender, i.e., a PSB. This sequence may be entered by either the expiration of the path refresh timer or directly as the result of the Path_Refresh_Needed flag being turned on during the processing of a received *Path* message.

- Compute the IP TTL for the *Path* message as one less than the maximum of the TTL values from the senders included in the message. However, if the result is zero, return without sending the *Path* message.
- Insert TIME_VALUES and PHOP objects into the *Path* message being built.
- Create a **sender descriptor** containing the SENDER_TEMPLATE, SENDER_TSPEC, and POLICY_DATA objects, if present in the PSB, and pack it into the *Path* message being built.
- Pass any ADSPEC and SENDER_TSPEC objects present in the PSB to the traffic control call TC_Advertise. Insert the modified ADSPEC object that is returned into the *Path* message being built.
- If the PSB has the E_Police flag on and if interface OI is not capable of policing, turn the E_Police flag on in the *Path* message being built.
- Send a copy of the *Path* message to each interface in OutInterfact_list. Before sending each copy, insert into its PHOP object the interface address and the LIH for the interface.

RESV REFRESH

This sequence sends a reservation refresh towards a particular previous hop with IP address PH. This sequence may be entered by either the expiration of a reservation refresh timer or directly as a result of the Resv_Refresh_Needed flag being turned on by processing a *Resv* or *ResvTear* message.

In general, this sequence considers each of the PSB's with PHOP address PH. For a given PSB, it scans the RSBs for matching reservations and merges the styles, FLOWSPECs and Filter_spec_list's appropriately. It then builds a *Resv* message and sends it to PH. The details depend upon the attributes of the style(s) included in the reservations.

- Create an output message containing INTEGRITY (if supported), SESSION, RSVP_HOP, and TIME_VALUES objects.
- Determine the style for these reservations from the first RSB for the session, and move the STYLE object into the proto-message. (Note that the present set of styles are never themselves merged; if future styles can be merged, these rules will become more complex).
- If style is wildcard and if there are PSB's from more than one PHOP and if the multicast routing protocol does not use shared trees, set the Need_Scope flag on, otherwise set it off.
- Select each sender PSB whose PHOP has address PH.

  1. Set local flag B_Merge off.
  2. Select all RSB's whose Filter_spec_list's match the SENDER_TEMPLATE object in the PSB and whose OI appears in the OutInterface_list of the PSB.
  3. If B_Merge flag is off then ignore a blockaded RSB, as follows.
     - Select BSB's that match this RSB; if any of these BSB's has a Qb that is not strictly larger than RSB Flowspec, then continue processing with the next RSB.

     However, if steps 1 and 2 result in finding that all RSB's matching this PSB are blockaded, then:
     - If this RESV REFRESH sequence was invoked from RESV ERROR RECEIVED, then return now to the latter.
     - Otherwise, turn on the B_Merge flag and restart with this procedure step 1. above.
  4. Merge the flowspecs, as follows:
     - If B_Merge flag is off, compute the LUB over the Flowspec objects of this set of RSB's.

       While computing the LUB, check for a RESV_CONFIRM object in each RSB. If a RESV_CONFIRM object is found:
       * If the FLOWSPEC in that RSB is larger than all other (non-blockaded) flowspecs being compared, then save this RESV_CONFIRM object for forwarding.
       * Otherwise (the corresponding FLOWSPEC is not the largest) then create and send a *ResvConf* message containing the RESV_CONFIRM object to the address in the RESV_CONFIRM object. Include the RESV_CONFIRM object in the *ResvConf* message. The *ResvConf* message should also include an ERROR_SPEC object whose Error_Node parameter is IP address of OI from the RSB.
       * Then delete the RESV_CONFIRM object from the RSB.
     - Otherwise (B_Merge flag is on), compute the GLB over the Flowspec objects of this set of RSB's.

       While computing the GLB, check for a RESV_CONFIRM object in each RSB.

If one is found, delete it.

5. If the Need_Scope flag is on, compute a new SCOPE object as the union of the SCOPE objects found in the RSB's.
6. Merge the F_POLICY_DATA objects from the RSB's.
7. (All matching RSB's have been processed). The next step depends upon the style attributes.
8. Merge the matching FILTER_SPEC objects from this set of RSB's. For explicit sender selection (FF, SE) styles, use the SENDER_TEMPLATE as the merged FILTER_SPEC; for wildcard sender selection (WF) style, there is no filter spec to be merged.

   Distinct reservation (FF) style

   Use the Sender_Template as the merged FILTER_SPEC. Pack the merged (FLOWSPEC, FILTER_SPEC, F_POLICY_DATA) triplet into the message as a **flow descriptor**.

   Shared wildcard reservation (WF) style

   There is no merged FILTER_SPEC. Merge (take the maximum of) the merged FLOWSPECS from the RSB's, across all PSB's for PH.

   Shared distinct reservation (SE) style

   Using the Sender_Template as the merged FILTER_SPEC, form the union of the FILTER_SPECS obtained from the RSB's. Merge (take the maximum of) the merged FLOWSPECS from the RSB's, across all PSB's for PH.
9. If the Need_Scope flag is on, remove from the merged SCOPE object all sender addresses that do not match the set of PSB's for PH, and all senders addresses that are local. If the resulting set is empty, no *Resv* should be forwarded to this PHOP; return. Otherwise (set is not empty), move the new SCOPE object into the message.

- (All PSB's have been processed). If a shared reservation style is being built, move the final merged FLOWSPEC, F_POLICY_DATA, and FILTER_SPEC (if SE) objects into the message.
- If a RESV_CONFIRM object was saved earlier, copy it into the new *Resv* message and delete it from the RSB in which it was found.
- Set the RSVP_HOP object in the message to contain the IncInterface address through which it will be sent and the LIH from (one of) the PSB's.
- Send the message to the address PH.

PATH LOCAL REPAIR

The sequence is entered when RSVP learns from routing that the set of outgoing interfaces for some destination (G,DstPort) has changed.

- Wait for a delay time of W seconds [Section 3.5].
- For each session that exists for destination IP address G, execute the PATH REFRESH event sequence above for each sender (PSB) for that session.

5 Acknowledgments

The design of RSVP is based upon research performed in 1992-1993 by a collaboration including Lixia Zhang (Xerox PARC), Deborah Estrin (USC/ISI), Scott Shenker (Xerox PARC), Sugih Jamin (USC/Xerox PARC), and Daniel Zappala (USC). Sugih Jamin developed the first prototype implementation of RSVP and successfully demonstrated it in May 1993. Shai Herzog, and later Steve Berson, continued development of RSVP prototypes.

Since 1993, many members of the Internet research community have contributed to the design and development of RSVP; these include (in alphabetical order) Steve Berson, Bob Braden, Lee Breslau, Dave Clark, Deborah Estrin, Shai Herzog, Craig Partridge, Scott Shenker, John Wroclawski, and Daniel Zappala. In addition, a number of host and router vendors have made valuable contributions, particularly Fred Baker (Cisco), Mark Baugher (Intel), Don Hoffman (Sun), Steve Jakowski (NetManage), John Krawczyk (Bay Networks), and Bill Nowicki (SGI). Ron Frederick, Bobby Minnear, Eve Schooler, and Garrett Wollman did early interfacing of multicast applications to RSVP. Steve Deering, Bill Fenner, and Ajit Thyagarajan helped with the interface between RSVP and multicast routing.

A Object Definitions

C-Types are defined for the two Internet address families IPv4 and IP6. To accommodate other address families, additional C-Types could easily be defined. These definitions are contained as an Appendix, to ease updating.

All unused fields should be sent as zero and ignored on receipt.

A.1 SESSION Class

SESSION Class = 1.

- IPv4/UDP SESSION object: Class = 1, C-Type = 1

```
+-------------+-------------+-------------+-------------+
|             IPv4 DestAddress (4 bytes)                |
+-------------+-------------+-------------+-------------+
| Protocol Id |    Flags    |          DstPort          |
+-------------+-------------+-------------+-------------+
```

- IP/UDP SESSION object: Class = 1, C-Type = 2

```
+-------------+-------------+-------------+-------------+
|                                                       |
+                                                       +
|                                                       |
+               IP6 DestAddress (16 bytes)              +
|                                                       |
+                                                       +
|                                                       |
+-------------+-------------+-------------+-------------+
| Protocol Id |     Flags   |          DstPort          |
+-------------+-------------+-------------+-------------+
```

DestAddress

The IP unicast or multicast destination address of the session. This field must be non-zero.

Protocol Id

The IP Protocol Identifier for the data flow. This field must be non-zero.

Flags

0x01 = E_Police flag

The E_Police flag is used in *Path* messages to determine the effective "edge" of the network, to control traffic policing. If the sender host is not itself capable of traffic policing, it will set this bit on in *Path* messages it sends. The first node whose RSVP is capable of traffic policing will do so (if appropriate to the service) and turn the flag off.

0x10 = Non_RSVP flag

The Non_RSVP flag is turned on in the SESSION object of a *Path* message whenever the RSVP daemon detects that the previous RSVP hop included one or more non-RSVP-capable routers. This flag is forwarded hop-by-hop and passed to a receiver application. If it is on, it indicates to the application that even a successful reservation request may not install the requested QoS at every node along the path.

0x20 = Maybe_RSVP flag

The Maybe_RSVP flag is turned on in the SESSION object of a *Path* message whenever the RSVP daemon is unable to ascertain whether or not the previous hop included one or more non-RSVP-capable routers. This flag is forwarded hop-by-hop and passed to a receiver application. If it is on and the Non_RSVP flag is off, the application cannot tell whether or not a successful reservation request may not install the requested QoS at every node along the path.

DstPort

The UDP/TCP destination port for the session. Zero may be used to indicate 'none'.

Other SESSION C-Types could be defined in the future to support other demultiplexing conventions in the transport-layer or application layer.

A.2 RSVP_HOP Class

RSVP_HOP class = 3.

- IPv4 RSVP_HOP object: Class = 3, C-Type = 1



- IP6 RSVP_HOP object: Class = 3, C-Type = 2



This object provides the IP address of the interface through which the last RSVP-knowledgeable hop forwarded this message. The Logical Interface Handle is a 32-bit number which may be used to distinguish logical outgoing interfaces as described in Section 3.2; it should be identically zero if there is no logical interface handle.

A.3 INTEGRITY Class

INTEGRITY class = 4.

See [Baker96].

A.4 TIME_VALUES Class

TIME_VALUES class = 5.

- TIME_VALUES Object: Class = 5, C-Type = 1



Refresh Period

The refresh timeout period R used to generate this message; in milliseconds.

A.5 ERROR_SPEC Class

ERROR_SPEC class = 6.

- IPv4 ERROR_SPEC object: Class = 6, C-Type = 1



- IP6 ERROR_SPEC object: Class = 6, C-Type = 2



Error Node Address

The IP address of the node in which the error was detected.

Flags

0x01 = InPlace

This flag is used only for an ERROR_SPEC object in a *ResvErr* message. If it on, this flag indicates that there was, and still is, a reservation in place at the failure point.

0x02 = NotGuilty

This flag is used only for an ERROR_SPEC object in a *ResvErr* message, and it is only set in the interface to the receiver application. If it on, this flag indicates that the

FLOWSPEC that failed was strictly greater than the FLOWSPEC requested by this receiver.

Error Code

A one-octet error description.

Error Value

A two-octet field containing additional information about the error. Its contents depend upon the Error Type.

The values for Error Code and Error Value are defined in Appendix B.

A.6 SCOPE Class

SCOPE class = 7.

This object contains a list of IP addresses, used for routing messages with wildcard scope without loops. The addresses must be listed in ascending numerical order.

- IPv4 SCOPE List object: Class = 7, C-Type = 1



- IP6 SCOPE list object: Class = 7, C-Type = 2



A.7 STYLE Class

STYLE class = 8.

- STYLE object: Class = 8, C-Type = 1



Flags: 8 bits

(None assigned yet)

Option Vector: 24 bits

A set of bit fields giving values for the reservation options. If new options are added in the future, corresponding fields in the option vector will be assigned from the least-significant end. If a node does not recognize a style ID, it may interpret as much of the option vector as it can, ignoring new fields that may have been defined.

The option vector bits are assigned (from the left) as follows:

19 bits: Reserved

2 bits: Sharing control

00b: Reserved
01b: Distinct reservations
10b: Shared reservations
11b: Reserved

3 bits: Sender selection control

000b: Reserved
001b: Wildcard
010b: Explicit
011b - 111b: Reserved

The low order bits of the option vector are determined by the style, as follows:

```
WF 10001b
FF 01010b
SE 10010b
```

A.8 FLOWSPEC Class

FLOWSPEC class = 9.

- Class = 9, C-Type = 2: int-serv flowspec

  The contents of this object will be specified in documents prepared by the int-serv working group.

A.9 FILTER_SPEC Class

FILTER_SPEC class = 10.

- IPv4 FILTER_SPEC object: Class = 10, C-Type = 1



- IP6 FILTER_SPEC object: Class = 10, C-Type = 2



- IP6 Flow-label FILTER_SPEC object: Class = 10, C-Type = 3



SrcAddress

The IP source address for a sender host. Must be non-zero.

SrcPort

The UDP/TCP source port for a sender, or zero to indicate 'none'.

Flow Label

A 24-bit Flow Label, defined in IP6. This value may be used by the packet classifier to efficiently identify the packets belonging to a particular (sender− >destination) data flow.

A.10 SENDER_TEMPLATE Class

SENDER_TEMPLATE class = 11.

- IPv4/UDP SENDER_TEMPLATE object: Class = 11, C-Type = 1
  Definition same as IPv4/UDP FILTER_SPEC object.
- IP6/UDP SENDER_TEMPLATE object: Class = 11, C-Type = 2
  Definition same as IP6/UDP FILTER_SPEC object.

A.11 SENDER_TSPEC Class

SENDER_TSPEC class = 12.

- Intserv SENDER_TSPEC object: Class = 12, C-Type = 1
  The contents of this object are specified in service specification documents prepared by the int-serv working group.

A.12 ADSPEC Class

ADSPEC class = 13.

- Intserv ADSPEC object: Class = 13, C-Type = 2

  The contents of this object are specified in service specification documents prepared by the int-serv working group.

A.13 POLICY_DATA Class

POLICY_DATA class = 14.

- Type 1 POLICY_DATA object: Class = 14, C-Type = 1
  The contents of this object are for further study.

A.14 RESV_CONFIRM Class

RESV_CONFIRM class = 15.

- IPv4 RESV_CONFIRM object: Class = 15, C-Type = 1



- IP6 RESV_CONFIRM object: Class = 15, C-Type = 2



B Error Codes and Values

The following Error Codes may appear in ERROR_SPEC objects and be passed to end systems. Except where noted, these Error Codes may appear only in *ResvErr* messages.

- Error Code = 00: Confirmation

  This code is reserved for use in the ERROR_SPEC object of a *ResvConf* message. The Error Value will also be zero.

- Error Code = 01: Admission Control failure

  Reservation request was rejected by Admission Control due to unavailable resources.

  For this Error Code, the 16 bits of the Error Value field are:

  ssur cccc cccc cccc

  where the bits are:

  ss = 00: Low order 12 bits contain a globally-defined sub-code (values listed below).

  ss = 10: Low order 12 bits contain a organization-specific sub-code. RSVP is not expected to be able to interpret this except as a numeric value.

  ss = 11: Low order 12 bits contain a service-specific sub-code. RSVP is not expected to be able to interpret this except as a numeric value.

  Since the traffic control mechanism might substitute a different service, this encoding may include some representation of the service in use.

  u = 0: RSVP rejects the message without updating local state.

  u = 1: RSVP may use message to update local state and forward the message. This means that the message is informational.

  r: Reserved bit, should be zero.

  cccc cccc cccc: 12 bit code.

  The following globally-defined sub-codes may appear in the low-order 12 bits when ssur = 0000:

  - Sub-code = 1: Delay bound cannot be met
  - Sub-code = 2: Requested bandwidth unavailable

- Error Code = 02: Policy Control failure

Reservation has been rejected for administrative reasons, for example, required credentials not submitted, insufficient quota or balance, or administrative preemption. This Error Code may appear in a *PathErr* or *ResvErr* message.

Contents of the Error Value field are to be determined in the future.

- Error Code = 03: No path information for this Resv message.

  No path state for this session. *Resv* message cannot be forwarded.

- Error Code = 04: No sender information for this Resv message.

  There is path state for this session, but it does not include the sender matching some **flow descriptor** contained in the *Resv* message. *Resv* message cannot be forwarded.

- Error Code = 05: Conflicting reservation style

  Reservation style conflicts with style(s) of existing reservation state. The Error Value field contains the low-order 16 bits of the Option Vector of the existing style with which the conflict occurred. This *Resv* message cannot be forwarded.

- Error Code = 06: Unknown reservation style

  Reservation style is unknown. This *Resv* message cannot be forwarded.

- Error Code = 07: Conflicting dest port

  Sessions for same destination address and protocol have appeared with both zero and non-zero dest port fields. This Error Code may appear in a *PathErr* or *ResvErr* message.

- Error Code = 08: Ambiguous path

  Sender port appears both zero and non-zero in same session in a *Path* message. This Error Code may appear only in a *PathErr* message.

- Error Code = 09, 10, 11: (reserved)

- Error Code = 12: Service preempted

  The service request defined by the STYLE object and the **flow descriptor** has been administratively preempted.

  For this Error Code, the 16 bits of the Error Value field are:

  ssur cccc cccc cccc

  Here the high-order bits ssur are as defined under Error Code 01. The following globally-defined sub-codes may appear in the low-order 12 bits when ssur = 0000 are to be defined in the future.

- Error Code = 13: Unknown object class

  Error Value contains 16-bit value composed of (Class-Num, C-Type) of unknown object. This error should be sent only if RSVP is going to reject the message, as determined by the

high-order bits of the Class-Num. This Error Code may appear in a *PathErr* or *ResvErr* message.

- Error Code = 14: Unknown object C-Type

  Error Value contains 16-bit value composed of (Class-Num, C-Type) of object.

- Error Code = 15-19: (reserved)

- Error Code = 20: Reserved for API

  Error Value field contains an API error code, for an API error that was detected asynchronously and must be reported via an upcall.

- Error Code = 21: Traffic Control Error

  Reservation request was rejected by Traffic Control due to the format or contents of the request. This *Resv* message cannot be forwarded, and continued attempts would be futile.

  For this Error Code, the 16 bits of the Error Value field are:

  ss00 cccc cccc cccc

  Here the high-order bits ss are as defined under Error Code 01.

  The following globally-defined sub-codes may appear in the low order 12 bits (cccc cccc cccc) when ssr = 000:

  - Sub-code = 01: Service conflict
    Trying to merge two incompatible service requests.
  - Sub-code = 02: Service unsupported
    Traffic control can provide neither the requested service nor an acceptable replacement.
  - Sub-code = 03: Bad Flowspec value
    Mal-formed or unreasonable request.
  - Sub-code = 04: Bad Tspec value
    Mal-formed or unreasonable request.

- Error Code = 22: Traffic Control System error

  A system error was detected and reported by the traffic control modules. The Error Value will contain a system-specific value giving more information about the error. RSVP is not expected to be able to interpret this value.

- Error Code = 23: RSVP System error

  The Error Value field will provide implementation-dependent information on the error. RSVP is not expected to be able to interpret this value.

In general, every RSVP message is rebuilt at each hop, and the node that creates an RSVP message is responsible for its correct construction. Similarly, each node is required to verify the correct construction of each RSVP message it receives. Should a programming error allow an RSVP to create a malformed message, the error is not generally reported to end systems in an ERROR_SPEC object; instead, the error is simply logged locally, and perhaps reported through network management mechanisms.

The only message formatting errors that are reported to end systems are those that may reflect version mismatches, and which the end system might be able to circumvent, e.g., by falling back to a previous CType for an object; see code 12 and 13 above.

The choice of message formatting errors that an RSVP may detect and log locally is implementation-specific, but it will typically include the following:

- Wrong-length message: RSVP Length field does not match message length.
- Unknown or unsupported RSVP version.
- Bad RSVP checksum
- Illegal RSVP message Type
- Illegal object length: not a multiple of 4, or less than 4.
- Next hop/Previous hop address in HOP object is illegal.
- Conflicting source port: Source port is non-zero in a filter spec or sender template for a session with destination port zero.
- Required object class (specify) missing
- Illegal object class (specify) in this message type.
- Violation of required object order
- Flow descriptor count wrong for style
- Logical Interface Handle invalid
- Unknown object Class-Num.

C UDP Encapsulation

An RSVP implementation will generally require the ability to perform "raw" network I/O, i.e., to send and receive IP datagrams using protocol 46. However, some important classes of host systems may not support raw network I/O. To use RSVP, such hosts must encapsulate RSVP messages in UDP.

The basic UDP encapsulation scheme makes two assumptions:

1. All hosts are capable of sending and receiving multicast packets if multicast destinations are to be supported.
2. The first/last-hop routers are RSVP-capable.

A method of relaxing the second assumption is given later.

Let Hu be a "UDP-only" host that requires UDP encapsulation, and Hr a host that can do raw network I/O. The UDP encapsulation scheme must allow RSVP interoperation among an arbitrary topology of Hr hosts, Hu hosts, and routers.

Resv, *ResvErr*, *ResvTear*, and *PathErr*messages are sent to unicast addresses learned from the path or reservation state in the node. If the node keeps track of which previous hops and which interfaces need UDP encapsulation, these messages can be sent using UDP encapsulation when necessary. On the other hand, *Path* and *PathTear* messages are send to thedestination address for the session, which may be unicast or multicast.

The tables in Figures 13 and 14 show the basic rules for UDP encapsulation of *Path* and *PathTear* messages, for unicast DestAddress and multicast DestAddress, respectively. Under the 'Send' column, the notation is 'mode(destaddr, destport)'; destport is omitted for raw packets. The 'Receive' column shows the group that is joined and, where relevant, the UDP Listen port.

It is useful to define two flavors of UDP encapsulation, one to be sent by Hu and the other to be sent by Hr and R, to avoid double processing by the recipient. In practice, these two flavors are distinguished by differing UDP port numbers Pu and Pu'.

The following symbols are used in the tables.

- D is the DestAddress for the particular session.
- G* is a well-known group address of the form 224.0.0.x, i.e., a group that is limited to the local connected network. [TO BE DEFINED]

- Pu and Pu' are two well-known UDP ports for UDP encapsulation of RSVP. [TO BE DEFINED]
- Ra is the IP address of the router interface 'a'.
- Tr is the TTL value of the specific *Path* message.
- Router interface 'a' is on the local network connected to Hu and Hr.

RA indicates that the Router Alert option is sent.

```
UNICAST DESTINATION D:

                RSVP                RSVP
Node            Send                Receive
---        -------------          ---------------
Hu          UDP(D/Ra,Pu)           UDP(D,Pu)
               [Note 1]         and UDP(D,Pu')
                                      [Note 2]


Hr          Raw(D,Tr)[RA]          Raw()
             and if (UDP)       and UDP(D, Pu)
             then UDP(D,Pu')          [Note 2]
                                   (Ignore Pu')

R (Interface a):
            Raw(D,Tr)[RA]          Raw()
             and if (UDP)       and UDP(Ra, Pu)
             then UDP(D,Pu')       (Ignore Pu')
```

Figure 13: UDP Unicast Encapsulation Rules for Path Messages

[Note 1] Hu sends a unicast *Path* message either to the destination address D, if D is local, or to the address Ra of the first-hop router. Ra is presumably known to the host.

[Note 2] Here D is the address of the local interface through which the message arrived.

[Note 3] This assumes that the application has joined the group D.

A router may determine if its interface X needs UDP encapsulation by listening for UDP-encapsulated *Path* messages that were sent to either G* (multicast D) or to the address of interface X (unicast

```
MULTICAST DESTINATION D:

                RSVP                        RSVP
Node            Send                        Receive
---            -------------               -----------------
Hu              UDP(G*,Pu)                      UDP(D,Pu')
                                                    [Note 3]
                                           and UDP(G*,Pu)


Hr              Raw(D,Tr)[RA]                   Raw()
                 and if (UDP)              and UDP(G*,Pu)
                   then UDP(D,Pu')           (Ignore Pu')

R (Interface a):
                Raw(D,Tr)[RA]                   Raw()
                 and if (UDP)              and UDP(G*,Pu)
                   then UDP(D,Pu')           (Ignore Pu')
```

Figure 14: UDP Multicast Encapsulation Rules for Path Messages

D). There is one failure mode for this scheme: if no host on the connected network acts as an RSVP sender, there will be no *Path* messages to trigger UDP encapsulation. In this (unlikely) case, it will be necessary to explicitly configure UDP encapsulation on the local network interface of the router.

When a UDP-encapsulated packet is received, the IP TTL is not available to the application on most systems. The RSVP daemon that receives a UDP-encapsulated *Path* or *PathTear* message should therefore use the Send_TTL field of the RSVP common header as the effective receive TTL. This may be overridden by manual configuration.

We have assumed that the first-hop RSVP-capable router R is on the directly-connected network. There are several possible approaches if this is not the case.

1. Hu can send both unicast and multicast sessions to UDP(Ra,Pu) with TTL=Ta

   Here Ta must be the TTL to exactly reach R. If Ta is too small, the *Path* message will not reach R. If Ta is too large, multicast routing in R will forward the UDP packet into the Internet until its hop count expires. This will turn on UDP encapsulation between routers within the Internet, perhaps causing bogus UDP traffic. The host Hu must be explicitly configured with Ra and Ta.

2. A particular host on the LAN connected to Hu could be designated as an *RSVP relay host*. A relay host would listen on (G*,Pu) and forward any *Path* messages directly to R, although it would not be in the data path. The relay host would have to be configured with Ra and Ta.

References

[Baker96] Baker, Fred, *RSVP Cryptographic Authentication*, Internet Draft draft-ietf-rsvp-md5-01.txt, February 1996.

[ISInt93] Braden, R., Clark, D., and S. Shenker, *Integrated Services in the Internet Architecture: an Overview*, RFC 1633, ISI, MIT, and PARC, June 1994.

[CSZ92] Clark, D., Shenker, S., and L. Zhang, *Supporting Real-Time Applications in an Integrated Services Packet Network: Architecture and Mechanisms*, Proc. SIGCOMM '92, Baltimore, MD, August 1992.

[FJ94] Floyd, S. and V. Jacobson, *Synchronization of Periodic Routing Messages*, IEEE/ACM Transactions on Networking, Vol. 2, No. 2, April, 1994.

[Katz95] Katz, D., *IP Router Alert Option*, Internet Draft draft-katz-router-alert-01.txt, Cisco Systems, November 16, 1995.

[Partridge92] Partridge, C., *A Proposed Flow Specification*, RFC 1363, BBN, September 1992.

[IServ93] Shenker, S., Clark, D., and L. Zhang, *A Service Model for an Integrated Services Internet*, Work in Progress, October 1993.

[RSVP93] Zhang, L., Deering, S., Estrin, D., Shenker, S., and D. Zappala, *RSVP: A New Resource ReSerVation Protocol*, IEEE Network, September 1993.

[ServTempl95a] Shenker, S., *Network Element Service Specification Template*, Internet Draft draft-ietf-intserv-svc-template-00.txt, Integrated Services Working Group, March 1995.

[Shenker94] Shenker, S., "Two-Pass or Not Two-Pass", Current Meeting Report, RSVP Working Group, Proceedings of the Thirtieth Internet Engineering Task Force, Toronto, Canada, July 1994.

Security Considerations

See Section 2.8.

Authors' Addresses

Lixia Zhang
Xerox Palo Alto Research Center
3333 Coyote Hill Road
Palo Alto, CA 94304

Phone: (415) 812-4415
EMail: Lixia@PARC.XEROX.COM

Bob Braden
USC Information Sciences Institute
4676 Admiralty Way
Marina del Rey, CA 90292

Phone: (310) 822-1511
EMail: Braden@ISI.EDU

Steve Berson
USC Information Sciences Institute
4676 Admiralty Way
Marina del Rey, CA 90292

Phone: (310) 822-1511
EMail: Berson@ISI.EDU

Shai Herzog
USC Information Sciences Institute
4676 Admiralty Way
Marina del Rey, CA 90292
Palo Alto, CA 94304

Phone: (310) 822 1511
EMail: Herzog@ISI.EDU

Sugih Jamin
Computer Science Department

University of Southern California
Los Angeles, CA 90089-0871

Phone: (213) 740-6578
EMail: jamin@catarina.usc.edu